

CLEAN 13



NON ACID CLEANER CONCENTRATE

DANGER
May be corrosive to metals. Causes serious eye irritation.
May damage fertility or the unborn child.
KEEP OUT OF REACH OF CHILDREN
See back panel for further precautions and first aid instructions
Net Contents: 1 5 20 35 55 Gallons

CLEAN 13



**P.O. Box 245013
Milwaukee, WI 53224
(800) 776-7192
www.sharecorp.com**



Tough stains call for tough cleaners to remove them. Previously you've had to use harsh acids like hydrofluoric and sulfuric acid to remove oxidation from aluminum. Share Corporation is proud to present CLEAN 13. This heavy duty acid replacement product has the performance of hydrofluoric and sulfuric acids and a pH of less than 1, but is non-corrosive to skin, making it a much safer alternative. When used as an aluminum cleaner and brightener, CLEAN 13 quickly removes calcium, lime, scale and silicate-deposits as well as corrosion and oxidation to leave surfaces bright and clean. CLEAN 13 is ideal for use on aluminum trailer bodies, boats, building materials and most other exterior aluminum surfaces. CLEAN 13 also removes dust, dirt, grime, grease and oxidation from aluminum or copper coils as well as fins of cooling units and air conditioners for more efficient operation.

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep only in original container. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If exposed or concerned: Get medical advice/attention.

Absorb spillage to prevent material damage. Store locked up. Store in corrosive resistant container with a resistant inner liner.

*For industrial and commercial use only.
For additional information, see Safety Data Sheet.*

DIRECTIONS

Always test on an inconspicuous area prior to using CLEAN 13. Wear rubber gloves and goggles when handling. Use CLEAN 13 full strength for heavy duty cleaning. CLEAN 13 may be diluted with up to 5 parts of water for maintenance or light cleaning and brightening. Brush, spray, or swab onto the surface to be cleaned, allow to penetrate soils, and then rinse thoroughly with clean water. Use with care on painted surfaces.

Use plastic pails for diluting and disposing of excess solution immediately after use.

Do not use on anodized aluminum.

Dispose of contents/container to comply with local/regional/national/international regulations.

NFPA® Ratings

Health: 2; Flammability: 1; Reactivity: 0

INGREDIENTS/CAS Number:

Water/7732-18-5; Organic Acid Salt/Proprietary; Proprietary/Proprietary; Carbamide Dihydrogen Sulfate/21351-39-3; Mixture/Proprietary; Linear Alcohol Ethoxylate/34398-01-1



Please Recycle.

0105.042815