

# FLOATING LIFT STATION DEGREASER

## Sewage Build-up Remover

**Form:** Liquid

**Color:** Colorless

**Odor:** Characteristic Solvent

**pH:** No data available

**Solubility (in water):** Emulsifies  
**(in mineral spirits):** Soluble

**VOC Content (% by wt):** 5.15 estimated

**Flash Point (ASTM D-7821):** 90°F

**Specific Gravity:** 7.22 lbs/gal

**Density:** 0.87 g/ml

**Storage Stability (at 70°F):** 1 year

**Ingredients**

**C.A.S. #**

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics

.....	64742-47-8
Solvent Naphtha (Petroleum), Light Aliphatic	
.....	64742-89-8
Xylene .....	1330-20-7
Ethyl Benzene .....	100-41-4

- | <b>Other Uses...</b> |                                     |
|----------------------|-------------------------------------|
| •                    | <b>Engine Degreaser</b>             |
| •                    | <b>Rust Proof Remover</b>           |
| •                    | <b>Tar Remover</b>                  |
| •                    | <b>Waterless Wood Floor Cleaner</b> |
| •                    | <b>Garbage Truck Cleaner</b>        |
| •                    | <b>Carburetor Cleaner</b>           |
| •                    | <b>Grease Trap Degreaser</b>        |

**DIRECTIONS:** Use 1/2 gallon of FLOATING LIFT STATION DEGREASER per square foot of water surface. Apply when lift station is at lowest level by spraying or pouring down the wall of the lift station.

**NOTE:** Because FLOATING LIFT STATION DEGREASER is an emulsifiable solvent, care must be taken to prevent immediate mixing of the solvent and water. Direct pouring or splashing into the water will cause the degreaser to be dispersed before it can remove the grease, destroying its effectiveness.

<b>HMIS®</b>			<b>NFPA®</b>		
	Severe	4	Extreme		
Health .....	Serious	3	High	Health.....	2
Flammability .....	Moderate	2	Moderate	Flammability .....	3
Reactivity .....	Slight	1	Slight	Reactivity .....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None