



Safety Drain Opener & Drain Line Maintainer

- Quickly penetrates, liquefies and dissolves hair and other blockages
- Heavy, thick formula - clings to pipes for longer contact time

GETS RIGHT TO THE CLOG!

Odorless • Biodegradable

Safer and more effective than ordinary caustic and acid drain openers!

WARNING

Causes eye irritation.

KEEP OUT OF REACH OF CHILDREN

Net Contents: 1 □ 5 □ 20 □ 35 □ 55 □ Gallons



**P.O. Box 245013
Milwaukee, WI 53224
800.776.7192
www.sharecorp.com**

SPECIMEN LABEL

WARNING:

Causes eye irritation.

Wash thoroughly after handling.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical advice/attention.

DISPOSAL:

Offer empty container for recycling. If recycling is not available, discard container in trash.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

POWER PURGE is a new and exciting fast-acting high-alkaline drain opener that's been formulated with new technology making it more powerful than ordinary caustic and acid drain openers. It's much safer for the user - Non-irritating to the skin, has no odor, and even ships DOT non-hazardous. Its super-thick and heavy properties make it quickly sink and penetrate through standing water right to the clog. It clings to pipe surfaces creating more contact time - making it even more effective in dissolving clog-forming substances.



Please Recycle.

DIRECTIONS:

For Drain Blockages:

Pour ½ to 1 quart of **POWER PURGE** slowly and directly into the drain. Allow 30 minutes for **POWER PURGE** to work. For stubborn clogs, an additional application may be required. Flush with hot water.

For Drain Line Maintenance:

Pour ½ quart into each problem drain once a week or as necessary to maintain free-flowing drains and drain lines.

For Laterals:

Pour 1 gallon into the drain upstream and as close as possible to the obstruction.

For Sewer Mains:

Pour 2-4 gallons in manhole or drain upstream and as close to the obstruction as possible. For best results, use regularly to keep sewer mains open and free-flowing.

NFPA® Ratings

Health: 0; Flammability: 0; Reactivity: 0

Contains/CAS Number:

Water/7732-18-5; Trade Secret/Proprietary; Xanthan Gum/11138-66-2; Alcohol Ethoxylate/68439-46-3; Modified Magnesium Silicate/53320-86-8

0252.052615