

FOUR WAY ACTION

Penetrant & Rust Preventative

Form: Liquid

Color: Brown

Odor: Petroleum

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): 45.0

Flash Point (ASTM D-7821): 165°F

Specific Gravity: 0.82 g/cm³

Density: 6.84 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Petroleum Distillates.....64742-47-8
 Barium Compound.....No CAS Number

Great for...	
•	Mechanics
•	Machinists
•	Pipefitters
•	Assemblers
•	Plumbers
•	All maintenance functions
Provides protection for...	
•	Rifles
•	Fishing reels
•	Cables
•	Parts
•	Ignition systems
•	Fire hydrants

DIRECTIONS: Apply FOUR WAY ACTION generously to all surfaces requiring protection. May be applied by brushing, spraying, swabbing, or pouring. Reapply as needed when lubricating film has worn or weathered off.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection	Minimal	0	Insignificant	Special Precautions	None