

# SILT & SAND REMOVER

## Silt Suspending Agent



**Form:** Liquid

**Color:** Clear to hazy

**Odor:** None

**pH:** N/A

**Solubility (in water):** Soluble

**(in mineral spirits):** No data available

**VOC Content (% by weight):** 0%

**Flash Point (Closed Cup):** >200°F

**Specific Gravity:** 1.0 g/cm<sup>3</sup>

**Density:** 8.35 lbs/gal

**Storage Stability (at 70°F):** 1 year

**Ingredients**

**C.A.S. #**

Water.....	7732-18-5
Non-Ionic Water Soluble Polymer .....	Proprietary
DMDM Hydantoin .....	Mixture
1,1'-Oxydipropan-2-ol .....	110-98-5
1,2-Benzisothiazol-3(2H)-one .....	2634-33-5

**DIRECTIONS:** Use SILT & SAND REMOVER at the rate of 1/2 to 1 gallon for each 1000 gallons of flushing water. Best results are obtained, when a program of regular flushing of sewer lines is followed.

**RECOMMENDED DOSAGES PER 400 FEET:**

4" Line .....	2 to 4 gallons
6" Line .....	4 to 6 gallons
8" Line .....	6 to 8 gallons
10" Line .....	8 to 10 gallons

**Other Uses...**

- **Ditches**
- **Wet Wells**
- **Sludge Drying Beds**
- **Lift Stations**
- **Sumps**
- **Pit and Chemical Toilets**
- **Sewer Lines**
  
- **Dairy Processing Facilities will enjoy easy removal of milk stone with SILT AND SAND REMOVER.**

HMIS®				NFPA®	
		Severe 4	Extreme		
Health .....	0	Serious 3	High	Health.....	0
Flammability.....	0	Moderate 2	Moderate	Flammability.....	0
Reactivity.....	0	Slight 1	Slight	Reactivity.....	0
Personal Protection.....	None	Minimal 0	Insignificant	Special Precautions.....	None