

# SOY LIFT

## Floating Lift Station Degreaser



**Form:** Liquid

**Color:** Green

**Odor:** Apple

**pH:** N/A

**Solubility (in water):** Negligible  
**(in mineral spirits):** Soluble

**Viscosity (CPS at 70°F):** >40

**Flash Point (ASTM D-7821):** >300°F

**Specific Gravity:** 0.88 ± 0.05 g/cm<sup>3</sup>

**Density:** 7.34 ± 0.05 lbs/gal

**VOC Content (% by wt):** 1.00-10.00

**Ingredients**

**C.A.S. #**

Methyl Ester of Soy Oil.....67784-80-9  
 Green Apple Perfume .....No CAS #  
 Oil Green Dye.....No CAS #

Use SOY LIFT In:	
•	<b>Wet Wells</b>
•	<b>Sewage Treatment Plants</b>
•	<b>Grease Traps</b>
•	<b>Vault Toilets</b>
•	<b>Sanitary &amp; Storm Sewers</b>

**DIRECTIONS:** Use 1/2 gallon of EARTH'S OWN – SOY LIFT for each square foot of water surface area. Spray or pour directly down side of lift station walls when water level is at its lowest. It is recommended to maintain a 1 to 2 inch layer of EARTH'S OWN – SOY LIFT on the surface at all times.

**WARNING:** Float valves must be adjusted to prohibit EARTH'S OWN – SOY LIFT from coming in contact with submerged pumps. Failure to do so could result in serious damage to pump.

HMIS				NFPA	
		Severe	4	Extreme	
Health.....0		Serious	3	High	Health ..... 0
Flammability .....1		Moderate	2	Moderate	Flammability..... 1
Reactivity .....0		Slight	1	Slight	Reactivity..... 0
Personal Protection.....X		Minimal	0	Insignificant	Special Precautions.....None