

# SOYABLE TAR REMOVER

## Natural Emulsifiable Tar Remover



**Form:** Liquid

**Color:** Colorless

**Odor:** Apple

**pH:** N/A

**Solubility (in water):** Emulsifiable  
**(in mineral spirits):** Soluble

**Viscosity (CPS at 70°F):** >40

**Flash Point (ASTM D-7821):** >300°F

**Specific Gravity:** 0.88 ± 0.05 g/cm<sup>3</sup>

**Density:** 7.34 ± 0.05 lbs/gal

**VOC Content (% by wt):** 5.00-15.00

### Ingredients

### C.A.S. #

Methyl Ester of Soy Oil.....67784-80-9

Linear Alcohol Ethoxylate.....34398-01-1

Green Apple Perfume .....No CAS #

### For Use By:

- **Public Works Departments**
- **Asphalt Paving Companies**
- **Trucking Companies**
- **Mining Operations**
- **Automotive Detail & Repair Shops**

### **DIRECTIONS:**

Apply EARTH'S OWN - SOYABLE TAR REMOVER to the affected area in concentrated form with a 3 gallon pressure sprayer, or by mopping on the surface. Allow time to penetrate and dissolve the tar, asphalt, or bituminous deposits for approximately 5 to 10 minutes, then rinse off with water under pressure.

HMIS			NFPA		
Health.....0	Severe 4	Extreme	Health.....0		
Flammability.....1	Serious 3	High	Flammability.....1		
Reactivity.....0	Moderate 2	Moderate	Reactivity.....0		
Personal Protection.....X	Slight 1	Slight	Special Precautions.....None		
	Minimal 0	Insignificant			