

DR-OP

Granular Drain Opener

Form: Pellets w/Aluminum Granules

Color: Yellow

Odor: None

pH: 14.0

Solubility (in water): Soluble
(in mineral spirits): Insoluble

VOC Content (% by weight): 0

Flash Point (ASTM D-7821): None

Specific Gravity: N/D

Density: N/D

Storage Stability (at 70°F): 1 year

Ingredients

	<u>C.A.S. #</u>
Sodium Hydroxide.....	1310-73-2
Sodium Nitrate.....	7631-99-4
Aluminum Granules	NO CAS #

Effective For...
<ul style="list-style-type: none"> • Fats • Grease • Soap • Hair • Proteins • Paper

IMPORTANT: READ ENTIRE LABEL CAREFULLY BEFORE USING. Use only as directed on the label. Any other use may result in serious personal injury or property damage.

DIRECTIONS: FOR SMALL DRAINS: Remove strainer or grate if possible. Remove excess water from bowl or trap. Water in drain should be cool. Carefully pour 1 ounce (2 tablespoons) of DR-OP into drain. Add 1 cup of COLD water to the drain immediately. If water boils out of drain, immediately add another cup of COLD water. After 15 minutes, flush drain with cold water. If drain is still clogged, repeat application.

FOR FLOOR DRAINS: Carefully follow the procedure above, but increase the dosage of DR-OP to 3 ounces and add 3 cups COLD water.

FOR PREVENTATIVE MAINTENANCE: Use DR-OP regularly to keep problem drains open and free-flowing. Carefully follow the directions given above.

HMIS			NFPA	
			Severe 4	Extreme
Health	3	Serious 3	High	Health
Flammability	0	Moderate 2	Moderate	Flammability.....
Reactivity	2	Slight 1	Slight	Reactivity.....
Personal Protection.....	X	Minimal 0	Insignificant	Special Precautions.....
				None