

DIESEL FUEL ANTI-GEL

Low Temperature Fuel Oil Additive

Form: Liquid

Color: Colorless, Clear to Hazy

Odor: Characteristic Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): N/D

Flash Point (Closed Cup): 120 °F

Specific Gravity: 0.89 g/cm³

Density: 7.43 lbs/gal

Storage Stability (at 70°F): 1 year

Excellent for use by...

- **Rail Fleet Operators**
- **Service Stations**
- **Fuel Oil Dealers**
- **Fuel Oil Haulers**
- **Boiler Operators**
- **Truck Fleet Operators**

Ingredients

C.A.S. #

Light aromatic solvent naphtha.....	64742-95-6
Benzene, trimethyl-.....	25551-13-7
1, 2, 4 - Trimethylbenzene	95-63-6
Heavy aromatic solvent.....	64742-94-5
Cumene	98-82-8

DIRECTIONS: Add 12 ounces of FUEL OIL ANTI-GEL to 150 gallons of fuel or 1 gallon to 1500 gallons of fuel.

This dosage will lower the pour point of most residual fuels by about 20 °F. In some cases, additional treatment will lower the pour point by several more degrees. For best results, fuels should be at 10 °F above the normal pour point when FUEL OIL ANTI-GEL is blended in.

HMIS®				NFPA®	
		Severe	4	Extreme	
Health	2	Serious	3	High	Health..... 2
Flammability	2	Moderate	2	Moderate	Flammability
Reactivity	0	Slight	1	Slight	Reactivity
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions
					None