

**SECTION 1: Product and company identification**

Product name : Diesel Klean  
Use of the substance/mixture : Fuel: additive  
Product code : 065701  
Company : Share Corporation  
P.O. Box 245013  
Milwaukee, WI 53224 - USA  
T (414) 355-4000  
Emergency number : Chemtrec: (800) 424-9300

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (GHS-US)**

Flam. Liq. 3 H226  
Acute Tox. 4 (Oral) H302  
Acute Tox. 4 (Inhalation) H332  
Skin Irrit. 2 H315  
Eye Irrit. 2B H320  
Muta. 1B H340  
Carc. 1B H350  
STOT SE 3 H335  
STOT SE 3 H336  
Asp. Tox. 1 H304

Full text of H-phrases: see section 16

**2.2. Label elements**

**GHS-US labeling**

Hazard pictograms (GHS-US) :



Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Flammable liquid and vapor  
Harmful if swallowed or if inhaled  
May be fatal if swallowed and enters airways  
Causes skin irritation  
Causes eye irritation  
May cause respiratory irritation  
May cause drowsiness or dizziness  
May cause genetic defects  
May cause cancer

Precautionary statements (GHS-US) :

Obtain special instructions before use  
Do not handle until all safety precautions have been read and understood  
Keep away from heat, open flames, sparks. - No smoking  
Keep container tightly closed  
Ground/bond container and receiving equipment  
Use explosion-proof electrical, lighting equipment  
Use only non-sparking tools  
Take precautionary measures against static discharge  
Avoid breathing fume, mist, spray, vapors  
Wash thoroughly after handling  
Do not eat, drink or smoke when using this product  
Use only outdoors or in a well-ventilated area  
Wear eye protection, protective clothing, protective gloves  
If swallowed: Immediately call a doctor, a POISON CENTER  
If swallowed: Call a doctor, a POISON CENTER if you feel unwell  
If on skin: Wash with plenty of soap and water.  
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
If inhaled: Remove person to fresh air and keep comfortable for breathing  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
If exposed or concerned: Get medical advice/attention  
Call a doctor, a POISON CENTER if you feel unwell

Specific treatment (see First aid measures on this label)  
 Rinse mouth  
 Do NOT induce vomiting  
 If skin irritation occurs: Get medical advice/attention  
 If eye irritation persists: Get medical advice/attention  
 Take off contaminated clothing and wash before reuse  
 In case of fire: Use carbon dioxide (CO<sub>2</sub>), dry extinguishing powder, foam to extinguish  
 Store in a well-ventilated place. Keep container tightly closed  
 Store in a well-ventilated place. Keep cool  
 Store locked up  
 Dispose of contents/container to comply with local/regional/national/international regulations.

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity (GHS US)**

Not applicable

**SECTION 3: Composition/information on ingredients**

**3.1. Substance**

Not applicable

Full text of H-phrases: see section 16

**3.2. Mixture**

Name	Product identifier	%	Classification (GHS-US)
SOLVESSO 100	(CAS No) 64742-95-6	50-90	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT SE 3, H336 STOT SE 3, H335 Asp. Tox. 1, H304
Trimethylbenzene	(CAS No) 25551-13-7	30-60	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Irrit. 2B, H320 Asp. Tox. 1, H304
1,2,4-trimethylbenzene	(CAS No) 95-63-6	15-40	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 STOT SE 3, H335 Aquatic Chronic 2, H411
2-ethylhexyl nitrate	(CAS No) 27247-96-7	5-10	Acute Tox. 4 (Inhalation), H332
cumene	(CAS No) 98-82-8	4-9	Flam. Liq. 3, H226 Carc. 2, H351 STOT SE 3, H335 Asp. Tox. 1, H304
xylene	(CAS No) 1330-20-7	0.5-5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Solvent naphtha (petroleum), heavy arom.; Kerosine - unspecified. [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C9 through C16 and boiling in the range of approximately 165 °C to 290 °C (330 °F to 554 °F).]	(CAS No) 64742-94-5	1-5	Asp. Tox. 1, H304
cymenes	(CAS No) 25155-15-1	0.5-1.5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Eye Irrit. 2A, H319
naphthalene	(CAS No) 91-20-3	0.1-1	Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Carc. 1B, H350 Aquatic Acute 1, H400

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
- First-aid measures after skin contact : Take off immediately all contaminated clothing and wash it before reuse. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention.

# Diesel Klean

## Safety Data Sheet



- First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Immediately call a poison center or doctor/physician. Rinse mouth with water. Do NOT induce vomiting.

### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : If you feel unwell, seek medical advice. Harmful if inhaled. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. May cause genetic defects (through prolonged or repeated exposure). May cause cancer.
- Symptoms/injuries after inhalation : Irritation of the respiratory tract. May cause drowsiness or dizziness. Central nervous system depression.
- Symptoms/injuries after skin contact : Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
- Symptoms/injuries after eye contact : Causes eye irritation.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. Risk of aspiration pneumonia. Gastrointestinal complaints. Cramps. Nausea. Vomiting.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical powder. Carbon dioxide. Alcohol-resistant foam.

### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable liquid and vapor.
- Explosion hazard : Vapors may travel long distances along ground before igniting/flashback to vapor source.
- Reactivity : Upon combustion: CO and CO<sub>2</sub> are formed.

### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Remove ignition sources. Use special care to avoid static electric charges.

#### 6.1.1. For non-emergency personnel

- Protective equipment : Protective goggles. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. No naked flames or sparks.

#### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers.
- Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation. Take up liquid spill into inert absorbent material, e.g.: sand/earth. Clean contaminated surfaces with a soap solution.

### 6.4. Reference to other sections

No additional information available

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Do not handle until all safety precautions have been read and understood. Do not breathe vapors. Use personal protective equipment as required. Do not eat, drink or smoke when using this product. Do not get in eyes, on skin, or on clothing. Handle and open the container with care. Keep away from sources of ignition - No smoking. Take precautions against electrostatic charges. Obtain special instructions before use. Remove contaminated clothing immediately.
- Hygiene measures : Wash thoroughly after handling. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Comply with applicable regulations. Proper grounding procedures to avoid static electricity should be followed.
Storage conditions	: Keep container tightly closed. Keep only in the original container in a cool, well ventilated place away from: sparks, open flames, excessive heat.
Incompatible products	: Strong oxidizers. acids.
Incompatible materials	: Sources of ignition. Heat sources.
Storage area	: Store away from heat. Store in a cool area. Store in a dry area. Store in a well-ventilated place. Keep locked up.
Special rules on packaging	: Keep only in original container. meet the legal requirements.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

naphthalene (91-20-3)		
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	ACGIH STEL (ppm)	10 ppm
ACGIH	Remark (ACGIH)	Hematologic eff; URT & eye irr; Skin; A3
1,2,4-trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm
ACGIH	ACGIH STEL (ppm)	25 ppm
cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	50 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & URT irr; CNS impair
xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair

### 8.2. Exposure controls

Personal protective equipment	: Use appropriate personal protective equipment when risk assessment indicates this is necessary. Gloves. Safety glasses. Protective goggles. Protective clothing.
-------------------------------	--



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear, gold liquid.
Odor	: solvent odor
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 108 °F Closed Cup
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available

# Diesel Klean

## Safety Data Sheet



Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.87 g/ml
Solubility	: Insoluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt
Viscosity, dynamic	: No data available
VOC content	: ND

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO2 are formed.

#### 10.2. Chemical stability

No additional information available

#### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

#### 10.4. Conditions to avoid

No additional information available

#### 10.5. Incompatible materials

Oxidizing agents. acids.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Inhalation:dust,mist: Harmful if inhaled.

<b>naphthalene (91-20-3)</b>	
LD50 oral rat	> 1100 mg/kg (Rat)
LD50 dermal rat	> 2500 mg/kg (Rat)
LD50 dermal rabbit	> 20000 mg/kg (Rabbit)
ATE CLP (oral)	500.000 mg/kg body weight
<b>2-ethylhexyl nitrate (27247-96-7)</b>	
LD50 oral rat	> 9640 mg/kg (Rat)
LD50 dermal rabbit	> 4820 mg/kg (Rabbit)
ATE CLP (gases)	4500.000 ppmV/4h
ATE CLP (vapors)	11.000 mg/l/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
<b>Trimethylbenzene (25551-13-7)</b>	
LD50 oral rat	500 mg/kg
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
<b>SOLVESSO 100 (64742-95-6)</b>	
LD50 oral rat	> 2000 mg/kg (Rat)
LD50 dermal rabbit	> 3160 mg/kg (Rabbit)
<b>xylene (1330-20-7)</b>	
LC50 inhalation rat (ppm)	4550 ppmV/4h
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4550.000 ppmV/4h

# Diesel Klean

## Safety Data Sheet



<b>xylene (1330-20-7)</b>	
ATE CLP (dust, mist)	1.500 mg/l/4h
<b>cymenes (25155-15-1)</b>	
LD50 oral rat	> 2000 mg/kg (Rat)
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.
<b>naphthalene (91-20-3)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
National Toxicology Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen
<b>cumene (98-82-8)</b>	
IARC group	2B - Possibly Carcinogenic to Humans
<b>xylene (1330-20-7)</b>	
IARC group	3 - Not Classifiable
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: May cause respiratory irritation. May cause drowsiness or dizziness.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: May be fatal if swallowed and enters airways.
Symptoms/injuries after inhalation	: Irritation of the respiratory tract. May cause drowsiness or dizziness. Central nervous system depression.
Symptoms/injuries after skin contact	: Causes skin irritation. Repeated exposure may cause skin dryness or cracking.
Symptoms/injuries after eye contact	: Causes eye irritation.
Symptoms/injuries after ingestion	: May be fatal if swallowed and enters airways. Risk of aspiration pneumonia. Gastrointestinal complaints. Cramps. Nausea. Vomiting.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>naphthalene (91-20-3)</b>	
LC50 fish 1	1.99 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	2.16 mg/l (48 h; Daphnia magna)
EC50 other aquatic organisms 1	2.96 mg/l (4 h; Selenastrum capricornutum)
LC50 fish 2	0.11 mg/l (96 h; Oncorhynchus mykiss)
TLM fish 1	150 mg/l (96 h; Lepomis macrochirus; Cool water)
TLM fish 2	1.24 ppm (96 h; Oncorhynchus gorboscha)
Threshold limit algae 1	0.4 mg/l (72 h; Skeletonema costatum; Growth rate)
<b>2-ethylhexyl nitrate (27247-96-7)</b>	
LC50 fish 1	116 mg/l 48 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 1	> 12.6 mg/l (48 h; Daphnia magna; Nominal concentration)
LC50 fish 2	145 mg/l 24 h; Salmo gairdneri (Oncorhynchus mykiss)
Threshold limit algae 1	3.22 mg/l (72 h; Pseudokirchneriella subcapitata; Growth rate)
<b>1,2,4-trimethylbenzene (95-63-6)</b>	
LC50 fish 1	7.72 mg/l (96 h; Pimephales promelas; Lethal)
LC50 fish 2	18 mg/l (48 h; Oryzias latipes)
Threshold limit algae 1	1 mg/l (72 h; Algae)
Threshold limit algae 2	2.356 mg/l (96 h; Algae)
<b>SOLVESSO 100 (64742-95-6)</b>	
LC50 fish 1	18 mg/l (Pisces)
EC50 Daphnia 1	21 mg/l (Daphnia sp.)
Threshold limit algae 1	1 - 10,Algae

### 12.2. Persistence and degradability

# Diesel Klean

## Safety Data Sheet



naphthalene (91-20-3)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Photolysis in the air.
Biochemical oxygen demand (BOD)	0 g O <sub>2</sub> /g substance
Chemical oxygen demand (COD)	0.22 g O <sub>2</sub> /g substance
ThOD	2.99 g O <sub>2</sub> /g substance
2-ethylhexyl nitrate (27247-96-7)	
Persistence and degradability	Not readily biodegradable in water.
1,2,4-trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O <sub>2</sub> /g substance
SOLVESSO 100 (64742-95-6)	
Persistence and degradability	Readily biodegradable in water.
cymenes (25155-15-1)	
Persistence and degradability	Biodegradability in water: no data available.

### 12.3. Bioaccumulative potential

naphthalene (91-20-3)	
BCF fish 1	23 - 168 (8 weeks; Cyprinus carpio)
BCF fish 2	40 - 300 (672 h; Oncorhynchus mykiss)
BCF other aquatic organisms 1	331 (360 h; Ostreidae)
BCF other aquatic organisms 2	130 (24 h; Chlorella sp.)
Log Pow	3.30 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
2-ethylhexyl nitrate (27247-96-7)	
Log Pow	5.24 (Test data; OECD 117: Partition Coefficient (n-octanol/water), HPLC method)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
1,2,4-trimethylbenzene (95-63-6)	
BCF fish 1	31 - 275 (8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
SOLVESSO 100 (64742-95-6)	
Log Pow	> 3
cymenes (25155-15-1)	
Bioaccumulative potential	No bioaccumulation data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.

## SECTION 14: Transport information

### Department of Transportation (DOT)

#### Additional information

Other information : When transported by ground in non-bulk containers, this product utilizes the exception found under 49 CFR 173.150.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

# Diesel Klean

## Safety Data Sheet



### SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

naphthalene	CAS No 91-20-3	0.1-1
1,2,4-trimethylbenzene	CAS No 95-63-6	15-40
cumene	CAS No 98-82-8	4-9
xylene	CAS No 1330-20-7	0.5-5
benzene	CAS No 71-43-2	< 50

naphthalene (91-20-3)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb

1,2,4-trimethylbenzene (95-63-6)	
Listed on SARA Section 313 (Specific toxic chemical listings)	

cumene (98-82-8)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb

xylene (1330-20-7)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity

### SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment - Chronic Hazard Category 2
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1B	Carcinogenicity Category 1B
Carc. 2	Carcinogenicity Category 2
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Eye Irrit. 2B	Serious eye damage/eye irritation Category 2B
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Muta. 1B	Germ cell mutagenicity Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed




# Diesel Klean

## Safety Data Sheet



H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H320	Causes eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*