

TRIDENT BOILERPRO FUEL PLUS

Combustion Catalyst

Form: Liquid

Color: Yellow

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): N/A

Flash Point (ASTM D-7821): 117°F

Specific Gravity: 0.88 g/cm³

Density: 7.34 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Light Aromatic	
Solvent Naphtha.....	64742-95-6
1,2,4 - Trimethylbenzene	95-63-6
Fuel Oil Conditioner	Proprietary
Corrosion Inhibitor	Proprietary
Xylene.....	1330-20-7

Ideal Uses...

- **Prevents the formation of sludge deposits**
- **Improves combustion**
- **Reduces emissions of SO₂ (sulfur dioxide) and SO₃ (sulfur trioxide)**
- **Protects against cold-end stack corrosion**
- **Retains a fluidizing effect at all temperatures for more uniform, faster pumping**

DIRECTIONS: It is advisable to add TRIDENT BOILERPRO FUEL PLUS directly to the fuel oil storage tank just before the tank is refilled so that incoming oil will provide sufficient agitation and mixing.

Initial dose: 2 gallons per 1000 gallons of fuel oil (1 quart per 125 gallons).

Maintenance dose: 1 quart per 1000 gallons of fuel oil (4 ounces per 125 gallons).

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	2
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None