

# Organic TAR REMOVER



**NATURAL CITRUS TAR REMOVER**  
CONTAINS NO PETROLEUM DISTILLATES OR CHLORINATED SOLVENTS

## DANGER

Flammable liquid and vapor. May be fatal if swallowed and enters airways.  
Causes skin irritation. May cause an allergic skin reaction.

**KEEP OUT OF REACH OF CHILDREN**

**NET CONTENTS: 1 5 20 35 55 Gallon(s)**

# Organic TAR REMOVER



**PO BOX 245013  
MILWAUKEE, WI 53224  
800.776.7192  
www.sharecorp.com**



**DANGER:**  
Flammable liquid and vapor. May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction.

**PREVENTION:**  
Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof ventilating, lighting, electrical equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

Store in a well-ventilated place. Keep cool. Store locked up.

Avoid breathing gas, mist, spray, vapors. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace.  
Wear protective gloves, protective clothing, eye protection, face protection.

**IF SWALLOWED:** Immediately call a POISON CENTER/doctor. Do NOT induce vomiting.

**IF ON SKIN (OR HAIR):** Take off immediately all contaminated clothing. Rinse skin with water/shower.

**If skin irritation or rash occurs:** Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

**IN CASE OF FIRE:**  
Use carbon dioxide (CO2), dry extinguishing powder, foam to extinguish.

**DISPOSAL:**  
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

*For industrial and commercial use only.*

*For additional information, see Safety Data Sheet.*

# Organic TAR REMOVER

**ORGANIC TAR REMOVER** utilizes the remarkable power of natural citrus extract to cut through the toughest dried tar, grease and asphalt deposits. It quickly penetrates, dissolves, and cleans without the hazards associated with petroleum distillates or chlorinated solvents. A built-in additive readily mixes with water for easy removal of deposits by high pressure water washing. **ORGANIC TAR REMOVER** is recommended for removal of road tar, asphalt, and grease from all municipal equipment. Regular applications are recommended for normal equipment maintenance. Effectively cleans boat and ship bilges. Removes sludge from oil tanks. Used by roofing contractors to clean tools and work areas. Also recommended for black-top contractors for tool and equipment maintenance.

**DIRECTIONS:**  
Apply **ORGANIC TAR REMOVER** to the affected area in concentrated form with a 3 gallon pressure sprayer, or by mopping on the surface. Allow time to penetrate and dissolve the tar, asphalt or bituminous deposits for approximately 5 to 10 minutes, then rinse off with water under pressure.

**NFPA® RATINGS:**  
Health: 1; Flammability: 2; Reactivity: 0

**INGREDIENTS/CAS #:**  
d-limonene/5989-27-5; Linear Alcohol Ethoxylates/34398-01-1; 1-Undecanol/112-42-5

1378.010815

