

**SECTION 1: Product and company identification**

Product name : Re-Flect  
 Use of the substance/mixture : Premoistened wipe  
 Product code : 154802  
 Company : Share Corporation  
 P.O. Box 245013  
 Milwaukee, WI 53224 – USA  
 T (414) 355-4000  
 Emergency number : Chemtrec: (800) 424-9300

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (GHS-US)**

Skin Sens. 1 H317  
 Asp. Tox. 1 H304  
 Full text of H-phrases: see section 16

**2.2. Label elements**

**GHS-US labeling**

Hazard pictograms (GHS-US) :

  
 GHS07

  
 GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : May be fatal if swallowed and enters airways  
 May cause an allergic skin reaction

Precautionary statements (GHS-US) : Avoid breathing fume  
 Contaminated work clothing must not be allowed out of the workplace  
 Wear eye protection, protective gloves  
 If swallowed: Immediately call a doctor, a POISON CENTER  
 If on skin: Wash with plenty of water  
 Do NOT induce vomiting  
 If skin irritation or rash occurs: Get medical advice/attention  
 Take off contaminated clothing and wash it before reuse  
 Store locked up  
 Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

**2.3. Other hazards**

No additional information available

**2.4. Unknown acute toxicity (GHS US)**

Not applicable

**SECTION 3: Composition/information on ingredients**

**3.1. Substance**

Not applicable  
 Full text of H-phrases: see section 16

**3.2. Mixture**

Name	Product identifier	%	Classification (GHS-US)
hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics	(CAS No) 64742-47-8	30 - 60	Flam. Liq. 4, H227 Asp. Tox. 1, H304
white mineral oil (petroleum)	(CAS No) 8042-47-5	15 - 40	Asp. Tox. 1, H304
(+)-limonene	(CAS No) 5989-27-5	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove the victim into fresh air.
- First-aid measures after skin contact : Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing.
- First-aid measures after ingestion : Rinse mouth with water. Do NOT induce vomiting. Immediately call a poison center or doctor/physician.

#### 4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
- Symptoms/injuries after inhalation : None under normal use.
- Symptoms/injuries after skin contact : May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.
- Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.
- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Foam. Carbon dioxide. Dry chemical powder.
- Unsuitable extinguishing media : Do not use extinguishing media containing water.

#### 5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible liquid.
- Reactivity : Upon combustion: CO and CO<sub>2</sub> are formed.

#### 5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Use water spray or fog for cooling exposed containers. Take account of environmentally hazardous firefighting water.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Isolate from fire, if possible, without unnecessary risk.

##### 6.1.1. For non-emergency personnel

- Protective equipment : Safety glasses. Gloves. Protective clothing.
- Emergency procedures : Evacuate unnecessary personnel. Avoid contact with skin, eyes and clothing. Ventilate spillage area.

##### 6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Stop leak if safe to do so. Stop release. Ventilate area.

#### 6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

#### 6.3. Methods and material for containment and cleaning up

- For containment : Contain released substance, pump into suitable containers.
- Methods for cleaning up : This material and its container must be disposed of in a safe way, and as per local legislation.

#### 6.4. Reference to other sections

No additional information available

### SECTION 7: Handling and storage

#### 7.1. Precautions for safe handling

- Precautions for safe handling : Comply with the legal requirements. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Do not eat, drink or smoke when using this product.
- Hygiene measures : Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

#### 7.2. Conditions for safe storage, including any incompatibilities

- Technical measures : Comply with applicable regulations.

# Re-Flect

## Safety Data Sheet



Storage conditions	: Store in a well-ventilated place. Keep cool. Store locked up.
Incompatible products	: Oxidizing agent.
Incompatible materials	: Sources of ignition. Heat sources.
Prohibitions on mixed storage	: KEEP SUBSTANCE AWAY FROM: oxidizing agents.
Storage area	: Meet the legal requirements.
Special rules on packaging	: meet the legal requirements.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

##### white mineral oil (petroleum) (8042-47-5)

ACGIH	ACGIH TWA (mg/m <sup>3</sup> )	5 mg/m <sup>3</sup>
-------	--------------------------------	---------------------

#### 8.2. Exposure controls

Personal protective equipment : Safety glasses. Gloves. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Premoistened wipe.
Odor	: Citrus scent
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 197 °F Closed cup - Tested using the liquid component of the towelette
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.81 g/ml - Tested using the liquid component of the towelette
Solubility	: Liquid component is not soluble in water.
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: < 20 cSt - Tested using the liquid component of the towelette
Viscosity, dynamic	: No data available
VOC content	: < 3 % - Tested using the liquid component of the towelette

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

Upon combustion: CO and CO<sub>2</sub> are formed.

#### 10.2. Chemical stability

No additional information available

### 10.3. Possibility of hazardous reactions

Refer to section 10.1 on Reactivity.

### 10.4. Conditions to avoid

No additional information available

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics (64742-47-8)</b>	
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Literature)
<b>(+)-limonene (5989-27-5)</b>	
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE CLP (oral)	4400.000 mg/kg body weight
<b>white mineral oil (petroleum) (8042-47-5)</b>	
LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat; Experimental value)

Skin corrosion/irritation : Not classified  
 Serious eye damage/irritation : Not classified  
 Respiratory or skin sensitization : May cause an allergic skin reaction.  
 Germ cell mutagenicity : Not classified  
 Carcinogenicity : Not classified

<b>(+)-limonene (5989-27-5)</b>	
IARC group	3 - Not Classifiable
<b>white mineral oil (petroleum) (8042-47-5)</b>	
IARC group	3 - Not Classifiable

Reproductive toxicity : Not classified  
 Specific target organ toxicity (single exposure) : Not classified  
 Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : May be fatal if swallowed and enters airways.  
 Symptoms/injuries after inhalation : None under normal use.  
 Symptoms/injuries after skin contact : May cause an allergic skin reaction. Repeated exposure may cause skin dryness or cracking.  
 Symptoms/injuries after eye contact : Direct contact with the eyes is likely irritating.  
 Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways.

## SECTION 12: Ecological information

### 12.1. Toxicity

<b>hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics (64742-47-8)</b>	
LC50 fish 1	> 100 mg/l (Pisces)
EC50 Daphnia 1	> 100 mg/l (Invertebrata)
Threshold limit algae 1	> 100 mg/l (Algae)
<b>(+)-limonene (5989-27-5)</b>	
LC50 fish 1	720 µg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 1	0.36 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	702 µg/l (96 h; Pimephales promelas)
Threshold limit algae 1	150 mg/l (72 h; Desmodesmus subspicatus; GLP)

# Re-Flect

## Safety Data Sheet



(+)-limonene (5989-27-5)	
Threshold limit algae 2	2.62 mg/l (72 h; Desmodesmus subspicatus)
white mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 100 mg/l (96 h; Oncorhynchus mykiss; Nominal concentration)
Threshold limit algae 1	>= 100 mg/l (72 h; Pseudokirchneriella subcapitata; Growth rate)

### 12.2. Persistence and degradability

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Persistence and degradability	Readily biodegradable in water. Adsorbs into the soil.
(+)-limonene (5989-27-5)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.
ThOD	3.29 g O <sub>2</sub> /g substance
white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water. No (test)data on mobility of the substance available.

### 12.3. Bioaccumulative potential

hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, < 2% aromatics (64742-47-8)	
Log Pow	6 - 8.2
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
(+)-limonene (5989-27-5)	
BCF fish 1	864.8 - 1022 (Pisces; Fresh weight)
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
white mineral oil (petroleum) (8042-47-5)	
Bioaccumulative potential	No bioaccumulation data available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods	: Do not flush wipes.
Waste disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations.

## SECTION 14: Transport information

### Department of Transportation (DOT)

In accordance with DOT : Not regulated for transport

#### Additional information

Other information : No supplementary information available.

#### ADR

No additional information available

#### Transport by sea

No additional information available

#### Air transport

No additional information available

## SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

California Proposition 65 - This product does not contain substances known to the state of California to cause cancer and/or reproductive toxicity

## SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

# Re-Flect


## Safety Data Sheet



### Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H317	May cause an allergic skin reaction

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.  
NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.  
NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.*