

# ZORBITALL

## Non-Selective Absorbent Powder

**Form:** Granular or Powder

**Color:** White

**Odor:** None

**pH:** N/A

**Solubility (in water):** Slight  
**(in mineral spirits):** Insoluble

**Flash Point (ASTM D-7821):** None

**Specific Gravity:** N/A

**Density:** 2.35 ± 0.05 lbs/gal

**Storage Stability (at 70°F):** 3 years

<u>Ingredients</u>	<u>C.A.S. #</u>
Perlite Ore .....	93763-70-3
Crystalline Silica Quarts .....	14808-60-7

<b>Great For...</b>	
•	<b>Automotive Fluids</b> (Fuels, Oils, Glycols, Brake, Transmission, Power Steering)
•	<b>Paints</b>
•	<b>Solvents</b>
•	<b>Caustics</b>
•	<b>Acids</b> (except Hydrofluoric)
•	<b>Great for use in any industry</b>

**DIRECTIONS:** Dispense Zorbitall in a circle around the spill to contain it. Use enough material to create a solid wall all the way around. Using a stiff bristled broom, work the Zorbitall slowly from the outside of the circle into the center. Allow the product time to absorb the liquid. Work the product back and forth with a swirling motion until surface is dry. Sweep up absorbent and place in a suitable container for disposal. Disposal of waste must be done in accordance with all applicable regulations.

<b>HMIS</b>				<b>NFPA</b>		
Health .....	1	Severe	4	Extreme	Health.....	1
Flammability.....	0	Serious	3	High	Flammability.....	0
Reactivity.....	0	Moderate	2	Moderate	Reactivity.....	0
Personal Protection.....	None	Slight	1	Slight	Special Precautions.....	None
		Minimal	0	Insignificant		