

# LIQUI-GEM DIAMOND

## Premium Grade Floor Finish

**Form:** Liquid

**Color:** Opaque White

**Odor:** Mild

**pH:** 8.0 – 9.0

**Solubility (in water):** Soluble  
**(in mineral spirits):** Insoluble

**Viscosity (CPS at 70°F):** >40

**Flash Point (ASTM D-7821):** N/A

**Specific Gravity:** 1.04 ± 0.05 g/cm<sup>3</sup>

**Density:** 8.68 ± 0.05 lbs/gal

**Storage Stability (at 70°F):** 1 year  
 (Damaged by freezing)

<u>Ingredients</u>	<u>C.A.S. #</u>
Diethylene Glycol Methyl Ether.....	111-77-3
Zinc Ammonium Carbonate .....	38714-47-5
Tributoxyethyl Phosphate .....	78-51-3
Dibutyl Phthalate .....	84-74-2

### Other DIAMOND Uses:

- Desk Top Sealer
- Quarry Tile Sealer
- Marble Polish
- Anti-Graffiti Coating
- Masonry Sealer
- Waterproofing Agent

**DIRECTIONS:** For best results, remove all previous finishes from floor. Apply 2 to 3 coats of DIAMOND, allowing at least 30 minutes of drying time between coats. For floors subject to burnishing operations, apply 4 to 6 coats of finish. Each layer of DIAMOND interlocks with the previous coat to form a thick cohesive film.

HMIS				NFPA	
		Severe	4	Extreme	
Health .....	1	Serious	3	High	Health .....
Flammability .....	0	Moderate	2	Moderate	Flammability .....
Reactivity .....	0	Slight	1	Slight	Reactivity .....
Personal Protection .....	X	Minimal	0	Insignificant	Special Precautions.....
					None