

ALL WEATHER PATCH

Paving Patch & Pot Hole Filler

Form: Viscous Liquid

Color: Black

Odor: Petroleum

pH: N/D

Solubility (in water): Negligible
(in mineral spirits): Soluble

Viscosity (cPs at 70°F): N/A

Flash Point (ASTM D-7821): 200°F min.

Specific Gravity: .99-1.03 /cm³

Density: 8.26-8.60 lbs/gal

Storage Stability (at 70°F): 2 years

<u>Ingredients</u>	<u>C.A.S #</u>
Asphalt	8052-42-4
Hydrogen Sulfide	7783-06-4
Petroleum Distillate	Mixture

Ideal for use on...
• Concrete
• Asphalt
• Brick Roads
• Stone Roads
• Parking Areas
• Playgrounds
• New and Used Car Lots
• Driveways

DIRECTIONS: Clean area to be repaired of debris. Fill with ALL WEATHER PATCH to about 2" above top of surface. Tamp down until packed firmly. Add additional amounts of ALL WEATHER PATCH to bring repaired area level to rest of surface.

HMIS				NFPA	
		Severe	4	Extreme	
Health	1	Serious	3	High	Health..... 1
Flammability	1	Moderate	2	Moderate	Flammability..... 1
Reactivity	0	Slight	1	Slight	Reactivity..... 0
Personal Protection	X	Minimal	0	Insignificant	Special Precautions.....None