



TUFF MOLY-5

WITH GRAPHITE

TUFF MOLY-5

WITH GRAPHITE

PREMIUM EXTREME PRESSURE HI-TEMPERATURE MULTI- PURPOSE GREASE

- **Calcium Sulfonate Complex Grease with Molybdenum & Graphite**
- **Temperature Range of -20° to 500° F**
 - **Extreme Pressure Additives For High Loads**
- **Superb Rust & Corrosion Inhibitors**
- **Resists: Acids, Water, Salt Spray, Dust & Dirt**

CAUTION:

**KEEP OUT OF REACH OF CHILDREN
SEE ADDITIONAL CAUTIONS ON BACK PANEL**

NET CONTENTS: 14 OZ. (397 g)

A multi-use grease containing moly, high viscosity base oil and calcium sulfonate thickener system for hundreds of automotive, marine, industrial and agricultural applications. Extreme pressure additives provide resistance to shock. Forms a protective film, resisting rust and corrosion. Resists chemical breakdown and oxidation. This water resistant lubricant will not wash out, and is resistant to corrosive salt water environments. Meets and exceeds the demanding automotive and industrial testing requirements of ASTM D 4950, earning it the GC-LB classification by the National Lubricating Grease Institute. This grease also meets Caterpillar CAT 5% moly requirements. Recommended for the most severe applications in off-highway construction, mining equipment, earth moving machines, Caterpillar equipment, as well as other heavy duty construction and mining equipment moving at slow to medium speed.

DIRECTIONS FOR USE: Pump in new grease until old grease comes out. Remove old grease if possible. For ball type grease fittings, fill until old grease comes out. Clean exposed areas with degreaser to remove old grease. Pump in new grease.

CAUTION: Keep out of reach of children. May cause irritation to eyes. Prolonged contact with skin may cause irritation. If ingested, may cause nausea, vomiting, and diarrhea. For eye contact, flush with water, see physician if oily film persists. For skin, wash with soap and water. For ingestion of more than 8 ounces contact physician.

CONTAINS (CAS#): Naphthenic Oil (64742-52-5); Graphite (7782-42-5); Molybdenum Disulfide (1317-33-5); Calcium Sulfonate Complex (N/A).

NLGI GRADE: 2

HMS Ratings: Health - 1; Flammability - 1; Reactivity - 0; Personal - A.

1845.110314