

Tough-Flex White

Safety Data Sheet



SECTION 1: Product and company identification

Product name : Tough-Flex White
Use of the substance/mixture : Adhesive
Product code : 187201
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224
T (414) 355-4000
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Liq. 4 H227
Resp. Sens. 1 H334
Carc. 2 H351

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Combustible liquid
May cause allergy or asthma symptoms or breathing difficulties if inhaled
Suspected of causing cancer

Precautionary statements (GHS-US) :

Obtain special instructions before use
Do not handle until all safety precautions have been read and understood
Keep away from heat, sparks, open flames, hot surfaces. - No smoking
Avoid breathing dust, fume, gas, mist, spray, vapors
Wear Use personal protective equipment as required
In case of inadequate ventilation wear respiratory protection
If inhaled: Remove person to fresh air and keep comfortable for breathing
If exposed or concerned: Get medical advice/attention
If experiencing respiratory symptoms: Call a doctor, a POISON CENTER
In case of fire: Use carbon dioxide (CO₂), dry extinguishing powder, foam to extinguish
Store in a well-ventilated place. Keep cool
Store locked up
Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
Limestone	(CAS No) 1317-65-3	10 - 30	Not classified
POLYVINYL CHLORIDE	(CAS No) 9002-86-2	10 - 30	Not classified
m-xylene	(CAS No) 108-38-3	1 - 5	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
Titanium Oxide	(CAS No) 13463-67-7	1 - 5	Carc. 2, H351
STEARIC ACID	(CAS No) 57-11-4	1 - 5	Not classified
propylene carbonate	(CAS No) 108-32-7	1 - 5	Not classified
IRON HYDROXIDE	(CAS No) 20344-49-4	1 - 5	Not classified

Tough-Flex White

Safety Data Sheet



Name	Product identifier	%	Classification (GHS-US)
ethylbenzene	(CAS No) 100-41-4	0.1 - 1	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation:vapour), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
p-xylene	(CAS No) 106-42-3	0.1 - 1	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
carbon black	(CAS No) 1333-86-4	0.1 - 1	Carc. 2, H351
Crystalline Silica	(CAS No) 14808-60-7	0.1 - 1	Carc. 1A, H350
4-isocyanatosulphonyltoluene, tosyl isocyanate	(CAS No) 4083-64-1	0.1 - 1	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Remove the victim into fresh air. If experiencing respiratory symptoms: Call a poison center or a doctor.
- First-aid measures after skin contact : Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Rinse mouth with water. Drink plenty of water. Never give anything by mouth to an unconscious person. Get medical advice/attention. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

No additional information available

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical powder. Carbon dioxide. Water fog. Alcohol-resistant foam.
- Unsuitable extinguishing media : Solid water jet ineffective as extinguishing medium.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Combustible.
- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

No additional information available

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : No flames, No sparks. Eliminate all sources of ignition.

6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment.
- Emergency procedures : Evacuate area. Keep upwind. No naked flames or sparks.

6.1.2. For emergency responders

- Protective equipment : Equip cleanup crew with proper protection.
- Emergency procedures : Ventilate area. Stop release. Stop leak if safe to do so.

6.2. Environmental precautions

Do not allow to enter drains or water courses. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

- For containment : Stop leak if safe to do so.
- Methods for cleaning up : Take up liquid spill into inert absorbent material. Collect spillage.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : Keep away from heat, sparks and flame.

Tough-Flex White

Safety Data Sheet



Precautions for safe handling : Do not breathe dust, fume, gas, mist, spray, vapors. Use only outdoors or in a well-ventilated area. Use personal protective equipment as required. Use only explosion-free electrical equipment with earth. Ground/bond container and receiving equipment. Take precautionary measures against static discharge.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Storage conditions : Keep cool. Store in a well-ventilated place. Keep container tightly closed. Store in original container.

SECTION 8: Exposure controls/personal protection


8.1. Control parameters

ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm
ACGIH	ACGIH STEL (ppm)	20 ppm
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
p-xylene (106-42-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
m-xylene (108-38-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
carbon black (1333-86-4)		
ACGIH	ACGIH TWA (mg/m ³)	3 mg/m ³ (Carbon black; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
Crystalline Silica (14808-60-7)		
OSHA	OSHA PEL (TWA) (mg/m ³)	0.1
POLYVINYL CHLORIDE (9002-86-2)		
ACGIH	ACGIH TWA (mg/m ³)	1 mg/m ³
ACGIH	Remark (ACGIH)	Varies Pneumoconiosis; LRT irr;

8.2. Exposure controls

Appropriate engineering controls : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Personal protective equipment : Gloves. Protective clothing. Protective goggles. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
 Appearance : Paste.
 Odor : Solvent-like odor
 Odor threshold : No data available
 pH : No data available
 Melting point : No data available
 Freezing point : No data available
 Boiling point : No data available
 Flash point : 165.9 °F
 Relative evaporation rate (butyl acetate=1) : No data available
 Flammability (solid, gas) : No data available

Tough-Flex White

Safety Data Sheet



Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 1.2 - 1.4 g/ml
Solubility	: No data available
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: 2.8 %

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Heat. Open flame. Sparks.

10.5. Incompatible materials

None known.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified

ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE CLP (oral)	3500.000 mg/kg body weight
ATE CLP (dermal)	15415.000 mg/kg body weight
ATE CLP (gases)	4000.000 ppmV/4h
ATE CLP (vapors)	17.800 mg/l/4h
ATE CLP (dust, mist)	17.800 mg/l/4h
p-xylene (106-42-3)	
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
m-xylene (108-38-3)	
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (dust, mist)	1.500 mg/l/4h
carbon black (1333-86-4)	
LD50 oral rat	> 8000 mg/kg (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 3000 mg/kg (Rabbit)

Skin corrosion/irritation : Not classified

Tough-Flex White

Safety Data Sheet



Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

ethylbenzene (100-41-4)	
IARC group	2B - Possibly Carcinogenic to Humans
carbon black (1333-86-4)	
IARC group	2B - Possibly Carcinogenic to Humans
Titanium Oxide (13463-67-7)	
IARC group	2B - Possibly Carcinogenic to Humans
Crystalline Silica (14808-60-7)	
IARC group	1 - Carcinogenic to Humans

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified.
Aspiration hazard	: Not classified

SECTION 12: Ecological information

12.1. Toxicity

ethylbenzene (100-41-4)	
LC50 fish 1	9.09 mg/l (96 h; Pimephales promelas)
EC50 Daphnia 1	77 mg/l (24 h; Daphnia magna)
EC50 other aquatic organisms 1	48 mg/l (72 h; Scenedesmus subspicatus)
LC50 fish 2	4.2 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	75 mg/l (48 h; Daphnia magna)
TLM fish 1	29 ppm (96 h; Lepomis macrochirus; Hard water)
TLM fish 2	42.3 mg/l (96 h; Pimephales promelas)
TLM other aquatic organisms 1	10 - 100,96 h
Threshold limit algae 1	> 160 mg/l (192 h; Scenedesmus quadricauda; Toxicity test)
Threshold limit algae 2	33 mg/l (192 h; Microcystis aeruginosa; Toxicity test)
carbon black (1333-86-4)	
LC50 fish 1	> 1000 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio)
EC50 Daphnia 1	> 5600 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 24 h; Daphnia magna; Static system; Fresh water)
LC50 fish 2	1000 mg/l (LC0; OECD 203: Fish, Acute Toxicity Test; 96 h; Brachydanio rerio; Semi-static system; Fresh water; Experimental value)
Threshold limit algae 1	> 10000 mg/l (EC50; OECD 201: Alga, Growth Inhibition Test; 72 h; Scenedesmus subspicatus; Static system; Fresh water; Experimental value)

12.2. Persistence and degradability

ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	(20 day(s)) 45.4
carbon black (1333-86-4)	
Persistence and degradability	Biodegradability: not applicable. Biodegradability in soil: not applicable. Adsorbs into the soil.
ThOD	Not applicable

12.3. Bioaccumulative potential

ethylbenzene (100-41-4)	
BCF fish 1	1 (6 weeks; Oncorhynchus kisutch)
BCF fish 2	15 - 79 (Carassius auratus)

Tough-Flex White

Safety Data Sheet



ethylbenzene (100-41-4)	
BCF other aquatic organisms 1	4.68 (Lamellibranchiata)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
carbon black (1333-86-4)	
Bioaccumulative potential	Not bioaccumulative.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : NA1993 Combustible liquid, n.o.s., 3, III
 UN-No.(DOT) : NA1993
 Proper Shipping Name (DOT) : Combustible liquid, n.o.s.
 Transport hazard class(es) (DOT) : 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
 Packing group (DOT) : III - Minor Danger
 DOT Packaging Non Bulk (49 CFR 173.xxx) : 203
 DOT Packaging Bulk (49 CFR 173.xxx) : 241
 DOT Symbols : D - Proper shipping name for domestic use only, or to and from Canada,G - Identifies PSN requiring a technical name
 DOT Special Provisions (49 CFR 172.102) : IB3,T1,T4,TP1
 DOT Packaging Exceptions (49 CFR 173.xxx) : 150
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L
 DOT Vessel Stowage Location : A

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

ethylbenzene	CAS No 100-41-4	0.1 - 1
p-xylene	CAS No 106-42-3	0.1 - 1
m-xylene	CAS No 108-38-3	1 - 5

ethylbenzene (100-41-4)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb
p-xylene (106-42-3)	

Tough-Flex White

Safety Data Sheet



p-xylene (106-42-3)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
m-xylene (108-38-3)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	1000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity


SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.

Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Inhalation:vapour)	Acute toxicity (inhalation:vapor) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Carc. 1A	Carcinogenicity Category 1A
Carc. 2	Carcinogenicity Category 2
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Resp. Sens. 1	Respiratory sensitisation Category 1
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H350	May cause cancer
H351	Suspected of causing cancer
H373	May cause damage to organs through prolonged or repeated exposure

- NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
- NFPA fire hazard : 2 - Must be moderately heated or exposed to relatively high temperature before ignition can occur.
- NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.