

SWEEPING COMPOUND OIL-BASED Treated Pine Sawdust

Form: Wood Dust

Color: Red

Odor: Slight Oil

pH: N/A

Solubility (in water): N/A
(in mineral spirits): N/A

Viscosity (CPS at 70°F): N/A

Flash Point (ASTM D-7821): 345°F

Specific Gravity: 1.50 ± 0.05 g/cm³

Density: 12.52 ± 0.05 lbs/gal

Storage Stability (at 70°F): 2 years

Use on...	
•	Painted Cement
•	Painted Wood
•	Sealed Wood
•	Linoleum
•	Ceramic Tile
•	Mosaic Tile
•	Other Fine Finishes

Ingredients

C.A.S. #

Wood Dust NO CAS #
Naphthenic Distillate NO CAS #

DIRECTIONS: Sprinkle SWEEPING COMPOUND OIL-BASED at one end of floor and sweep across. Never spread SWEEPING COMPOUND OIL-BASED over the entire floor.

HMIS		NFPA				
Health	0	Severe	4	Extreme	Health.....	0
Flammability.....	0	Serious	3	High	Flammability.....	0
Reactivity.....	0	Moderate	2	Moderate	Reactivity.....	0
Personal Protection	X	Slight	1	Slight	Special Precautions	None
		Minimal	0	Insignificant		