



TRIDENT

WATER TREATMENT

BOILERPRO S

SOFT WATER WATER TREATMENT

PROVIDES SUPERIOR PROTECTION IN SOFT WATER SYSTEMS
PREVENTS LIME, SCALE, RUST AND MINERAL DEPOSITS

DANGER

Causes severe skin burns and eye damage
May be corrosive to metals.

KEEP OUT OF REACH OF CHILDREN

NET CONTENTS: 1 5 20 35 55 Gallon(s)

TRIDENT

WATER TREATMENT

BOILERPRO S



P.O. Box 245013

Milwaukee, WI 53224

(800) 776-7192

www.sharecorp.com



Keep only in original container. Do not breathe mist, spray. Wash thoroughly after handling. Wear eye protection, protective clothing, protective gloves. Wash contaminated clothing before reuse.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a doctor, a POISON CENTER.

Store locked up. Store in corrosive resistant container with a resistant inner liner.

Dispose of contents/container to comply with local/regional/national/international regulations.

For industrial and commercial use only.

For additional information, see Safety Data Sheet.

NFPA RATINGS:

Health: 2; Flammability: 0; Reactivity: 0

CONTAINS/CAS#:

Water/7732-18-5; Proprietary/Mixture;
Tetrapotassium Pyrophosphate/7320-34-5;
Potassium Hydroxide/1310-58-3; Sodium
Lignosulfonate/8061-51-6

WARNING:

This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

1958.050715

TRIDENT BOILERPRO S is a phosphate-based liquid steam boiler additive fortified with a proven polymeric scale inhibitor that works especially well in soft water environments. It is safe to use with other boiler treatment chemicals, especially steam line treatments and oxygen scavengers.

DIRECTIONS:

The dosage of **TRIDENT BOILERPRO S** will depend on the percent of condensate returned, makeup water characteristics and initial cleanliness of heat transfer surfaces. The treatment program must be accompanied by a program of regular blowdown to remove sludge and suspended solids from the boiler. **TRIDENT BOILERPRO S** may be fed on a "one shot" basis or with an automated continuous system. Gradual and continuous feeding is recommended for industrial processes and other large boilers. **TRIDENT BOILERPRO S** may be mixed with other boiler treatment chemicals, especially a steam line treatment and oxygen scavengers where needed, and diluted with water for convenient feeding. If the boiler water system has not been previously treated, add a starting dosage or twice the amount recommended for weekly dosages for the first four weeks.

For weekly maintenance: Add 1/2 gallon (2 quarts) of TRIDENT BOILERPRO S per week for each 25 horsepower of boiler capacity, or 1 gallon for every 125 gallons of boiler water capacity. This use rate may vary due to feedwater hardness and differences in a boiler's rated horsepower versus the boiler's operational horsepower. Control the level of **TRIDENT BOILERPRO S** by maintaining the hydroxide (OH) alkalinity level between 150-250ppm.

Blowdown: Open the blowdown valve until the level drop in the sight glass is reached. Recommended starting point is 2 inches twice a week. Blowdown schedules will vary depending upon water hardness and permissible cycles of concentration.



Please Recycle.

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com