

RUBBER IN A CAN

Protective Flexible Rubber Coating

Form: Aerosol Liquid

Color: Opaque, black

Odor: Solvent

pH: N/A

Solubility (in water): Negligible
(in mineral spirits): No data available

VOC Content (% by weight): 22.5

Flash Point: -156°F (Propellant)

Specific Gravity: 1.037 g/ml

Density: 8.65 lbs/gal

Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Calcium Carbonate.....	1317-65-3
Toluene	108-88-3
Methyl Acetate	79-20-9
Acetone	67-64-1
Solvent Naptha.....	64742-94-5

Great for use on...

- **Concrete and Asphalt Driveways**
- **Gutters and Flashings**
- **HVAC Equipment**
- **Construction Equipment**
- **Roofs**
- **Gas Tanks**
- **Trunk Decks**
- **Underbodies and Fender and Panel Replacements**

DIRECTIONS: SHAKE WELL BEFORE USING. Make sure surface is clean, dry and free of dirt and rust. Hold can 12 inches from surface. Spray a thin even coat building up to the desired thickness. Remove overspray with a cloth dampened with kerosene.

Coverage: 10 to 20 square feet per can.

Temperature: Both surface and at use temperature should be between -10°F to 150°F.

HMIS®				NFPA®	
		Severe	4	Extreme	
Health	2	Serious	3	High	Health..... 2
Flammability	4	Moderate	2	Moderate	Flammability..... 4
Reactivity	0	Slight	1	Slight	Reactivity..... 0
Personal Protection.....	X	Minimal	0	Insignificant	Special Precautions.....None