

HI TEMP RED GREASE AEROSOL

Multi-Service Non-Melt Lubricant

Form: Liquid

Color: Red

Odor: Petroleum

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): 49.0%

Flash Point (ASTM D-7821): >200°F

Specific Gravity: 0.92 g/cm³

Density: 7.68 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Heptane	142-82-5
Heavy Naphthenic Petroleum Distillate	64742-52-5
Propane/n-Butane.....	68476-86-8
Tetrachloroethylene	127-18-4
Organophilic Clay	No CAS Number

Great for...

- **Farms**
- **Oil rigs**
- **Refineries**
- **Bottling plants**
- **Paper mills**
- **Cotton gins**
- **Industrial plants**
- **Cement plants**
- **Marine applications**
- **Motorcycle applications**
- **Automotive applications**

Provides protection for...

- **Cables**
- **Rollers**
- **Winches**
- **Gears**
- **Springs**
- **Couplings**
- **Power Mowers**
- **And much more...**

DIRECTIONS: Shake Well Before Using. Remove cap and hold can approximately 6 to 8 inches from surface to be sprayed. Apply a light coat by spraying in quick short bursts. Work part to distribute HI TEMP RED GREASE AEROSOL evenly over the entire surface. For hard-to-reach areas, insert the red extender tube into the tip. Spray as necessary to insure complete coverage. Temperatures over 375°F may require periodic reapplication.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	3
Reactivity.....	Slight	1	Slight	Reactivity.....	1
Personal Protection	Minimal	0	Insignificant	Special Precautions	None