

# CEILING TILE WHITENER

## New White Acoustical Tile Rejuvenator

**Form:** Aerosol Liquid

**Color:** White

**Odor:** Hydrocarbon

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Not determined

**VOC Content (% by weight):** 51

**Flash Point (ASTM D-7821):** Not determined

**Specific Gravity:** 0.87 g/ml

**Density:** 7.26 lbs/gal

**Storage Stability (at 70°F):** 1 year

Use it to cover...	
•	<b>Water Spots</b>
•	<b>Stains</b>
•	<b>Blackening Around Air Conditioning Ducts</b>
•	<b>Any Acoustical Tile Discoloration</b>

<u>Ingredients</u>	<u>C.A.S. #</u>
Propane/n-Butane.....	68476-86-8
Isoparaffinic Hydrocarbon .....	64742-47-8
Acetone .....	67-64-1
Titanium Dioxide .....	13463-67-7
Ethyl Alcohol .....	64-17-5

**DIRECTIONS:** Clean surface thoroughly to remove grease, dust and other foreign matter. Shake can vigorously before and during use. From a distance of 12 inches, spray to coat surface lightly. Allow to dry, then follow with another light coat. Apply at temperatures above 65°F. One can covers 12-15 (2' x 4') tiles or 120 square feet. NOTE: Following use, invert can and spray a short burst to clear nozzle for storage. If nozzle becomes clogged, remove and hold under running warm water.

HMIS®				NFPA®	
		Severe	4	Extreme	
Health .....	2	Serious	3	High	Health..... 2
Flammability .....	3	Moderate	2	Moderate	Flammability .....
Reactivity .....	0	Slight	1	Slight	Reactivity .....
Personal Protection .....	X	Minimal	0	Insignificant	Special Precautions .....
					None