



HI-YO SILVER

Protective Flexible Durable Silver Coating

USE FOR SEALING:

**Leaky roofs, edges & flashings,
window sills, PVC pipes, A/C Drip Pans,
duct work, chimneys, foundations,
trailers and more!**

**Coating remains flexible and
will not crack or peel!
Protects against corrosion!**

DANGER:

EXTREMELY FLAMMABLE LIQUID AND VAPOR.
VAPORS MAY CAUSE FLASH FIRE. CONTENTS UNDER PRESSURE.
VAPOR HARMFUL. See other cautions on back panel.

NET WEIGHT: 15 OZ. (425 g)

Share's HI-YO SILVER is a unique spray product that leaves a firm coating which stays flexible. Will not sag or drip. The coating is impervious to water. The film will not freeze or crack in cold, is abrasion resistant and won't peel. Economical, quick, and easy to use. Seals out rust and corrosion.



DANGER:

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure.

PREVENTION:

Pressurized container: do not pierce or burn, even after use. Use only with adequate ventilation. Do not breathe dust/vapors/spray mist. Avoid contact with eyes/skin/clothing. Wear protective gloves/clothing/glasses. Keep away from heat/sparks/open flames/hot surfaces. Do not eat/drink/smoke when using this product. Do not spray on naked flame or other ignition sources.

RESPONSE:

In case of fire, use extinguishing powder or water spray. Immediately contact a doctor or POISON CONTROL CENTER if you feel unwell. If medical attention is needed, have product label at hand.

IF IN EYES:

Rinse with water for several minutes. Remove contact lenses if present. If eye irritation persists seek medical attention.

IF SWALLOWED:

Rinse mouth with water. Do not induce vomiting.

IF INHALED:

Remove to fresh air.

IF ON SKIN:

Wash thoroughly with water. Remove all contaminated clothing.

STORAGE:

Store locked up. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F.

DISPOSAL:

Dispose of product in accordance with local/regional/national/international regulations.

PRECAUTION STATEMENTS:

Vapors may ignite explosively and cause a flash fire. Prevent buildup of vapors by opening windows and doors to achieve cross ventilation. Reports have associated repeated and prolonged occupational over-exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately inhaling the contents may be harmful or fatal. In cases where short and/or long term overexposure conditions exist, a charcoal filter respirator should be worn. Follow respirator manufacturer's directions for use.

CONTAINS:

VM&P Naphtha (64742-89-8); Toluene (108-88-3); Propane (74-98-6); Heptane (142-82-5); N-Butane (106-97-8); Talc (14807-96-6); Acetone (67-64-1); Xylene (1330-20-7); Aluminum Flake (7429-90-5); PM Acetate (108-65-6); Mineral Spirits (64742-47-8); Isobutyl Acetate (110-19-0). OTHER INGREDIENTS: "Contents Partially Unknown", Sebs Rubber.

DIRECTIONS:

1. Surface must be clean and dry before painting. Protect surrounding areas from spray mist. For best results, use when can is between 50°F and 90°F (10°C and 32°C).
2. Shake can at least one minute after rattle is heard and occasionally during use.
3. Spray surface with steady even strokes at a distance of 2 to 10 inches (5 to 25cm). Multiple coats may be applied, allowing 20 to 30 minutes between coats.
4. If clogging develops, turn sprayhead 1/4 turn or remove and clean sprayhead slot. DO NOT stick pin or other objects into can opening. With can and sprayhead pointed away from you, reinsert sprayhead with a gentle twisting motion.
5. To clear sprayhead for future use, turn can upside down and spray for 3 seconds. Completely empty cans may be recycled or disposed of with regular trash. Dispose of partially empty cans responsibly. DO NOT incinerate or compact.

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

KEEP OUT OF REACH OF CHILDREN

SOLD BY:

8036.021419

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com