



SILICONE RTV CLEAR

SEALER · CAULKER · ADHESIVE

100% R.T.V. SILICONE INDUSTRIAL STRENGTH

TEMPERATURE RANGE: -60°F TO 450°F

CAULKS AROUND TUBS, SINKS, SHOWERS

INSULATES ELECTRICAL COMPONENTS

SEALS AROUND
WINDOWS, DOORS, WALLS, ETC.

BONDS MOST MATERIALS,
SIMILAR OR DISSIMILAR

GLASS • WOOD • METAL • RUBBER • PLASTIC • ETC.

WARNING

Contains gas under pressure; may explode if heated. Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling Causes serious eye irritation. Causes skin irritation. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

KEEP OUT OF REACH OF CHILDREN

NET WT. 8 oz. (226g)

SILICONE RTV-CLEAR is ideal for use wherever a strong, permanently elastic weatherproof adhesive, sealant or caulk is needed. This product has excellent adhesion characteristics, high chemical resistance and will not sag or shrink due to severe temperature extremes.

This product meets the requirement of FDA Regulation No. 21CFR 177.2600, when fully cured and washed. This formulation has been certified to Federal Specification TT-S-001543A Class A (COM-NBS). TT-S-00230 Class A (COM-NBS) for silicone building sealants and MIL-A-46106A. Amend. 2, Type1. Do not use for HEAD GASKETS.

This sealant is not paintable. If painting is required, complete before using this product. This product is not suitable for below waterline marine applications. When finished leave a small bead of material on tip to act as a sealing "plug". If plug breaks leaving the dispensing tip sealed, use a paper clip or other wire object to remove and loosen the remainder of the cured material.

WARNING:

Contains gas under pressure; may explode if heated. Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling Causes serious eye irritation. Causes skin irritation. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

PREVENTION:

Wear protective gloves. Wear eye or face protection. Wash hands thoroughly after handling.

RESPONSE:

IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

STORAGE:

Protect from sunlight. Store in a well-ventilated place.

INGREDIENTS/CAS#:

Triacetoxymethylsilane (17689-77-9);
Methylsilanetriyl triacetate (4253-34-3);
1,1-Difluoroethane (75-37-6)

DIRECTIONS:

1. Clean and dry surface. Remove oil, grease or soap from surface.
2. Hold nozzle at a 45° angle and apply in any direction.
3. Sealant normally "skins over" in 5 minutes and dries tack free to the touch in one hour. If spreading or working material is required do immediately after applying. Paper towels can be used to remove excess.
4. Sealant cures and bonds fully in 24 hours and maximum strength is achieved in 7 days.
5. For food use sealant must be washed thoroughly before use. Sealant is easily trimmed with a sharp tool. Do not destroy bond by undercutting.



8051.021115