



SILICONE LUBRICANT

ALL PURPOSE DRY LUBRICANT RELEASE AGENT

- For industrial and commercial use
- Stops sticking drawers, windows, doors, screens, zippers and blocks
- Fast drying

DANGER: EXTREMELY FLAMMABLE
HARMFUL OR FATAL IF SWALLOWED. VAPORS HARMFUL.
CONTENTS UNDER PRESSURE. KEEP OUT OF REACH OF CHILDREN.

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONS.

Net Wt. 13 oz. (369 g)

SILICONE LUBRICANT is a dry silicone lubricant formulated to stop sticking, binding and squeaking. It is a unique formulation of a reacted-grade silicone and fast-evaporating solvents, with fine-mist spray pattern that allows for even and controlled silicone distribution. When used as directed does not cause "fish eyes" in paint, and is therefore useful in auto-body shops, mold-release, and other applications where paintability is required. **SILICONE LUBRICANT** is also excellent for metal-to-metal, aluminum, rubber & plastic lubrication, thread & fiber lubes, and rubber & plastic mold release applications.

APPLICATIONS:

Automotive: Lubricates window channels, door, weather stripping, trunk seals, under-carriage, rubber mounting, emergency brakes, pedal shafts, car seats, adjustment mechanism. Eliminates squeaks from fan belts (do not apply when running). Prevents battery terminal corrosion. Waterproofs ignition system, hinges, springs and casters.

Packaging: Prevents waxes, adhesives and plastics from sticking to heat sealer bars. Reduces clean-up time. Eliminates friction on guide rails, line conveyors, scramble tables, etc.

Garments: Promotes slip on sewing machine beds, cutting tables and dies. Prevents bunching of fabrics during sewing operation.

Plastic Molding: Release agent for injection and compression moldings.



DANGER:

Keep out of reach of children. Read label and SDS before use. Extremely flammable aerosol. Contains gas under pressure, may explode if heated. May be fatal if swallowed and enters airways. May cause drowsiness or dizziness. Causes skin irritation. Causes serious eye irritation.

PREVENTION:

Avoid breathing mist/spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Do not spray on open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Wash hands thoroughly after handling. Wear protective gloves. Wear eye protection.

DIRECTIONS:

Thoroughly clean surface to be sprayed. Hold the **SILICONE LUBRICANT** can 8" to 10" from surface. Spray lightly with a sweeping motion. Avoid overspraying. On sticking parts, work back and forth to allow good penetration. Wipe off excess with a clean cloth.

INGREDIENTS/CAS#:

Heptane (142-82-5); Propane (74-98-6); Butane (106-97-8); Silicone Fluid (68952-01-2)

NFPA® RATINGS:

Health: 2; Flammability: 4;
Reactivity: 0; Maximum Personal Protection: G

RESPONSE:

IF SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation occurs get medical attention. Take off contaminated clothing and wash it before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF eye irritation persists: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a POISON CENTER or a doctor if you feel unwell.

STORAGE:

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Store locked up. Dispose of contents and container in accordance with all local, regional, and national regulations.



Nonfood Compounds
H2
NO FOOD CONTACT



Please Recycle.

Sold by:

8098.100815

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com