

SILICONE LUBRICANT

Dry-Film Silicone Lubricant



Form: Liquid
Color: Colorless
Odor: Solvent
pH: N/A
Solubility (in water): Insoluble
(in mineral spirits): Soluble
VOC Content (% by weight): ~97.0 %
Flash Point (ASTM D-7821): 0°F
Specific Gravity: 0.77 g/cm³
Density: 6.43 lbs/gal
Storage Stability (at 70°F): 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
Heptane	142-82-5
N-Butane (Propellant).....	106-97-8
Propane	74-98-6
Silicone Fluid.....	68952-01-2

Great to use for...

- **Mold release**
- **Textile industry**
- **Automotive industry**
- **Vending equipment**
- **Molding equipment**
- **Dry cleaning equipment**
- **Packaging & processing industry**

Provides Protection for...

- **Lock mechanisms**
- **Movable parts**
- **Cutting tables**
- **Hinges**
- **Sewing machines**
- **Window and door seals**

DIRECTIONS: Thoroughly clean surface to be sprayed. Hold the SILICONE LUBRICANT can 8” to 10” from surface. Spray lightly with a sweeping motion. Avoid overspraying. On sticking parts, work back and forth to allow good penetration. Wipe off excess with a clean cloth.

HMIS				NFPA	
		Severe	4	Extreme	
Health	2	Serious	3	High	Health..... 2
Flammability.....	4	Moderate	2	Moderate	Flammability..... 4
Reactivity.....	0	Slight	1	Slight	Reactivity..... 0
Personal Protection.....	G	Minimal	0	Insignificant	Special Precautions.....None