



DI-LUBE

AEROSOL CUTTING & TAPPING LUBRICANT

**CLINGING FORMULA
STAYS ON CUTTING SURFACE**

DANGER

Extremely flammable aerosol. May cause cancer.

**KEEP OUT OF REACH OF CHILDREN
READ OTHER PRECAUTIONS ON BACK PANEL.**

NET WEIGHT: 12 oz.



DANGER:

Extremely flammable aerosol. May cause cancer.

PREVENTION:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, open flames, sparks. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container. Do not pierce or burn, even after use. Wear protective gloves, protective clothing, eye protection, face protection. **If exposed or concerned:** Get medical advice/attention.

Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents/container to comply with local/regional/national/international regulations.

DI-LUBE contains special extreme pressure additives to increase production and extend tool life. Use high performance **DI-LUBE** on high carbon steels, stainless and other hard alloys, as well as free-machining steels. The unique clinging formula stays on the cutting tool to provide excellent residual lubrication for cooler temperatures, cleaner cuts and smooth finished surfaces.

DI-LUBE is ideal for all milling, boring, cutting, tapping, threading, sawing and machining operations. This fluid allows better workpiece visibility and helps produce clean, sharp cuts.

INGREDIENTS/CAS#:

Solvent Refined, Hydrotreated Paraffinic Distillate (64742-54-7); Propane (74-98-6); Chloroparaffins, 70% chlorinated, liquid (63449-39-8); Heavy Naphthenic Distillate (64741-96-4).

NFPA® RATINGS:

Health: 1, Flammability: 4, Reactivity: 0

KEEP OUT OF REACH OF CHILDREN

Refer to SDS for further information.
For industrial and commercial use only.



Please Recycle.

Sold by:

8103.051215