

ARCTIC WRENCH

Rapid Freezing Aerosol Penetrant Lubricant

Form: Aerosol Liquid

Color: Colorless

Odor: Solvent

pH: N/D

Solubility (in water): Negligible

(in mineral spirits): Soluble

VOC Content (% by weight): 30.0 – 35.0

Specific Gravity: N/D

Density: N/D

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

1,1-Difluoroethane	75-37-6
Heptane	64742-49-0
Severely Hydrotreated Naphthenic Distillate.....	64742-52-5

For Use On...
• Rusted Manifold Bolts
• Exhaust Flanges
• Industrial Equipment
• Marine Equipment
• Farm Equipment
• Any Outdoor Equipment

DIRECTIONS: Shake well before using. Spray liberally on surface to be treated for 5-10 seconds. Limit the amount of contact to the surrounding area by targeting the bolt, nut or affected part. Wait 30 seconds to allow temperature reduction and to facilitate penetration. Loosen or remove part. Repeat if necessary.

Safe for use on many plastics and painted surfaces but be sure to always test ARCTIC WRENCH on an inconspicuous area prior to use. Sudden temperature drop may result in “thermal shock” causing crazing of some plastics and painted surfaces.

Always use product with adequate ventilation. Accumulated vapors from ARCTIC WRENCH could reach ignition conditions in a confined area.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	3
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None