

CHAIN & CABLE LUBE

Foaming Lubricant with Moly

Form: Liquid

Color: Black

Odor: Solvent

pH: N/A

Solubility (in water): Negligible
(in mineral spirits): Soluble

VOC Content (% by weight): 21.0%

Flash Point (ASTM D-7821): -156°F

Specific Gravity: 0.79 g/cm³

Density: 6.59 lbs/gal

Ingredients

C.A.S. #

Heavy Paraffinic	
Petroleum Distillate	64741-88-4
Mineral Spirits	64742-47-8
Stoddard Solvent.....	8052-41-3
Cocoyl Diethanolamide	68603-42-9
Propane	74-98-6

<p>Great for Use On...</p> <ul style="list-style-type: none"> • Wire ropes • Cables • Chain • Rollers • Pins • Bushings <p>Provides protection from...</p> <ul style="list-style-type: none"> • Friction • Wear • Rust • Corrosion • Vibrations • Chain whip and noise
--

DIRECTIONS: Shake until ball rattles for at least 30 seconds before applying. For best application, CHAIN & CABLE LUBE should be used at room temperature or at temperatures above 70 °F. Parts to be treated should be reasonably clean and dry. Hold can 12 to 14 inches from surface to be treated and spray to coat surface. Product will penetrate into tight spaces. Product will spray from any angle, even inverted.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	4
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection	Minimal	0	Insignificant	Special Precautions.....	None