

BLAST AWAY

Brake Parts Cleaner

Form: Liquid

Color: Water White

Odor: Chlorinated Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): >90

Viscosity (CPS at 70°F): >40

Flash Point (ASTM D-7821): >200

Specific Gravity: 1.46 ± 0.05 g/cm³

Density: 12.18 ± 0.05 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Trichloroethylene.....79-01-6
Carbon Dioxide (Propellant).....124-38-9

Other BLAST AWAY Uses

- **Tar Remover**
- **Ink Remover**
- **Paper Lint Remover**
- **Vending Machine Cleaner**
- **Typewriter Cleaner**
- **Clock Cleaner**
- **Adding Machine Cleaner**
- **HVAC Equipment Cleaner**

DIRECTIONS: Spray BLAST AWAY directly onto the brake assembly to remove accumulations of grime before beginning repair. Use the extension tube to assure a complete flushing of all moving parts before re-assembly. After assembly, spray brakes, pads, and friction surfaces to completely remove all traces of brake fluid.

HMIS			NFPA		
Health	2	Severe 4	Extreme	Health	2
Flammability.....	1	Serious 3	High	Flammability	1
Reactivity.....	0	Moderate 2	Moderate	Reactivity	0
Personal Protection	X	Slight 1	Slight	Special Precautions	None
		Minimal 0	Insignificant		