

GRAPHITE LUBRICANT AEROSOL

Dry-Film Lubricant

Form: Liquid

Color: Gray

Odor: Hydrocarbon

pH: N/A

Solubility (in water): Negligible
(in mineral spirits): Soluble

VOC Content (% by Weight): >90

Flash Point (ASTM D-7821): < -156

Specific Gravity: >1.00 g/cm³

Density: >8.35 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Toluene	108-88-3
Liquefied Petroleum Gas	68476-85-7
Graphite	7782-42-5
Paraloid	108-88-3

Great for...

- **Mechanics**
- **Pipefitters**
- **Plumbers**
- **Assemblers**
- **Maintenance personnel**

Provides protection for...

- **Drills**
- **Jigs**
- **Ladle Pins**
- **Guns**
- **Door Locks**
- **Rollers**
- **Conveyors**
- **Engine Blocks**
- **Windshield Wiper Arms**
- **Speedometer Cables**
- **And much more...**

DIRECTIONS: Shake well before using. Hold nozzle 8 to 12 inches from the surface to be treated. Spray GRAPHITE LUBRICANT AEROSOL to cover surface with a light, even mist. For hard-to-reach areas, insert extension tube in spray tip. Clean the spray nozzle thoroughly after each use by inverting can and pressing valve for 2 to 3 seconds.

Note: Suitable for use with operating temperatures ranging from -100°F to +800°F.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health.....	3
Flammability.....	Moderate	2	Moderate	Flammability.....	4
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None