

# ELEKTRACON

## Flammable Contact Cleaner

**Form:** Liquid

**Color:** Clear

**Odor:** Characteristic

**pH:** N/A

**Solubility (in water):** To 32 at 68°F  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** 75

**Flash Point (TAG CC):** 22°F

**Specific Gravity:** 0.71 g/cm<sup>3</sup>

**Density:** 5.95 lbs/gal

**Storage Stability (at 70°F):** 1 year

<u>Ingredients</u>	<u>C.A.S. #</u>
n-Heptane.....	142-82-5
2-Propanol.....	67-63-0
Ethanol.....	64-17-5
Methanol.....	67-56-1
n-Propyl Acetate.....	109-60-4
1,1-difluoroethane.....	75-37-6

### Uses...

- **Safe on Most Plastics**
- **Non-Corrosive**
- **Zero Residue**
- **Rapidly Evaporates**
- **Non-Ozone Depleting**
- **EPA SNAP Approved**

**DIRECTIONS:** Disconnect equipment from power source. Make sure opening of spray head is pointing toward surface to be cleaned. Hold can 6-8 inches away. Direct spray to saturate soiled surface. A brush may be utilized to help in the removal of heavy soils. Start at the top of area to be cleaned using a sweeping motion and spray the area, slowly working toward the bottom. To clean in hard to reach areas, insert extension tube in spray head to direct spray. **Allow components to dry completely before applying current.**

HMIS®			NFPA		
Health.....	1	Severe 4	Extreme	Health.....	1
Flammability.....	3	Serious 3	High	Flammability.....	3
Physical Hazard.....	0	Moderate 2	Moderate	Reactivity.....	0
Personal Protection.....	X	Slight 1	Slight	Special Precautions.....	None
		Minimal 0	Insignificant		