

GREASE IT AEROSOL

Bentone-based Red Grease



Form: Liquid

Color: Red

Odor: Solvent

pH: N/A

Solubility (in water): Insoluble
(in mineral spirits): Soluble

VOC Content (% by weight): 48.0%

Viscosity (CPS at 70°F): Slightly viscous

Flash Point (ASTM D-7821): <0°F

Specific Gravity: 0.78 g/cm³

Density: 6.51 lbs/gal

Storage Stability (at 70°F): 1 year

Use it to lubricate...

- Elevator Cables
- Window Slides
- Motorcycle Chains
- Garage Door Tracks
- Springs
- Couplings
- Power Mowers
- Tools
- Fork Lifts
- Conveyors
- Marine Motors
- Hinges

<u>Ingredients</u>	<u>C.A.S. #</u>
Hexane	110-54-3
Petroleum Distillates.....	8002-05-9
n-Butane.....	106-97-8
Propane	74-98-6
Red Grease.....	No CAS #

DIRECTIONS: Shake well before using. Spray a thin film on the surface to be lubricated or protected. To treat hard-to-reach areas, insert extension tube in spray tip. After using, clear valve by inverting can and spraying for a few seconds.

HMIS			NFPA		
	Severe	4	Extreme		
Health	Serious	3	High	Health	2
Flammability.....	Moderate	2	Moderate	Flammability.....	4
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None