



ANTI-SEIZE



***Non-Chlorinated
Extreme Temperature and
Extreme Pressure Lubricant***

**PROTECTS AGAINST
SEIZING • GALLING • CORROSION
GALVANIC PITTING • RUST
OF ALL THREADED PARTS**

Net Weight: 13 Oz. (369 g)

DANGER:
EXTREMELY FLAMMABLE AEROSOL.
CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
SEE OTHER CAUTIONS ON BACK PANEL.

KEEP OUT OF REACH OF CHILDREN

Contains No Chlorinated Solvents (No 1,1,1-Trichloroethane) Prevents galling, seizing, pitting, fretting, corrosion and distortion of threaded, keyed, splined and press fitted assemblies. Protects at sustained temperatures of up to 2000°F. Highly resistant to moisture, weather, chemical fumes, salt spray and steam. Allows tighter, more vibration-proof seals using less torque while making disassembly easier. USE ON: Industrial machinery, construction, farm, mining and earth moving equipment, marine hardware, vehicle fleets and assembly lines.



DANGER:

Extremely Flammable Aerosol. Contains gas under pressure; may explode if heated. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. Keep away from heat, sparks, open flames, and hot surfaces. -No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves.

FIRST AID:

If on skin: Wash with plenty of water.

If skin irritation occurs: Get medical advice or attention. Take off contaminated clothing and wash be-fore reuse. Avoid breathing mist, vapors or spray. Use only outdoors or in a well-ventilated place.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.

If swallowed: Immediately call a poison center or doctor. Do NOT induce vomiting. Dispose of contents and container in accordance with local, state, and federal regulations.

INGREDIENTS/CAS#:

Distillates (petroleum), hydrotreated heavy naphthenic (64742-52-5), Heptane (142-82-5), Propane (74-98-6), Butane (106-97-8), Aluminum (7429-90-5).

HMIS[®] RATINGS:

Health: 2; Flammability: 3; Physical Hazard: 0; Personal Protection: B

DIRECTIONS:

Preclean surfaces to be treated, removing any old contaminated grease, dirt or grit. Shake can thoroughly until agitator ball begins to rattle freely for at least 30 seconds. With can held in upright position, spray surface in short bursts from a distance of 8 to 10 inches. After use, invert can and clear actuator by spraying until only gas is dispelled.

CAUTIONS:

Use with adequate ventilation. Intentional misuse by concentrating and inhaling the product can be harmful or fatal. KEEP OUT OF REACH OF CHILDREN.

⚠ WARNING: This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

See Safety Data Sheet for complete safety information.

24 HOUR MEDICAL EMERGENCY: 1-866-836-8855 MADE IN THE USA

Sold by:

8223.012323

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com