

ANTI-SEIZE

Non-Chlorinated Extreme Pressure Lubricant

Form: Aerosol

Color: Thick Silver

Odor: Solvent

pH: N/A

Solubility (in water): Non-soluble

Flash Point (ASTM D-7821): N/A

Specific Gravity: N/A

Density: N/A

Storage Stability (at 70°F): 1 year+

This Product Contains: **CAS#**

Heptane	142-82-5
Propane	74-98-6
N-Butane	106-97-8
Aluminum	7429-90-5
Distillates hydrotreated light	64742-47-8

Great For Use In...

- Nuts, bolts, screws
- Hand & motor operated valves
- Electric motors
- Compressors
- Hoists, turbines, winches
- Furnaces
- Regulators, pumps & much more

Directions for Use: Shake can well before using. Clean surface thoroughly. Apply only enough to form a solid film over contact surfaces of threads, gaskets, bushings, etc. Assemble and wipe off excess.

CONSULT PRODUCT LABEL FOR DETAILED DIRECTIONS

HMIS			NFPA		
Health.....	2	Severe 4 Extreme	Health.....	2	
Flammability.....	3	Serious 3 High	Flammability.....	3	
Reactivity.....	0	Moderate 2 Moderate	Reactivity.....	0	
Personal Protection.....	B	Slight 1 Slight	Special Precautions.....	B	
		Minimal 0 Insignificant			