

# MOLY LUBE

## Dry Molybdenum Disulfide Aerosol Lubricant

**Form:** Liquid

**Color:** Dark Green / Black

**Odor:** Solvent

**pH:** N/A

**Solubility (in water):** Insoluble  
**(in mineral spirits):** Soluble

**VOC Content (% by weight):** 68.7%

**Viscosity (CPS at 70°F):** >40

**Flash Point (ASTM D-7821):** -141°F

**Specific Gravity:** 0.68 g/cm<sup>3</sup>

**Density:** 5.67 lbs/gal

**Storage Stability (at 70°F):** 1 year

<b>Ingredients</b>	<b>C.A.S. #</b>
Propane/Isobutane/n-Butane.....	68476-86-8
2-Propanol.....	67-64-1
Toluene.....	108-88-3
Isopropyl alcohol.....	67-63-0
Molybdenum disulfide.....	1317-33-5

### Other Uses...

- **Chain Lubrication**
- **Furnace Maintenance**
- **Gaskets**
- **Conveyors**
- **Kiln Maintenance**
- **Ovens**
- **Anti-seize Applications**
- **Mold Release Applications**

**DIRECTIONS:** SHAKE WELL BEFORE USING. For best results, apply to a dry, clean surface at room temperature. Shake until agitator ball rattles, then for 30 seconds more. Hold can 6 to 8 inches from surface and spray a thin, even film. Avoid spraying too thick, as this will decrease the effectiveness.

<b>HMIS</b>			<b>NFPA</b>		
Health.....	2	Severe 4	Extreme	Health.....	2
Flammability.....	4	Serious 3	High	Flammability.....	4
Reactivity.....	0	Moderate 2	Moderate	Reactivity.....	0
Personal Protection.....	X	Slight 1	Slight	Special Precautions.....	None
		Minimal 0	Insignificant		