

RYBS

Aerosol Extreme Temperature & Pressure Lubricant

Form: Solvent Base Aerosol

Color: Silver Gray

Odor: Ethereal Solvent

pH: None

Solubility (in water): None
(in mineral spirits): Soluble

VOC Content (% by weight): 41.36%

Flash Point (TCC): 122°F

Specific Gravity: 0.91 g/cm³

Density: 7.59 lbs/gal

Storage Stability (at 70°F): 1 year

Ingredients

	<u>C.A.S. #</u>
Aluminum	7429-90-5
Heptane	142-82-5
Hydrotreated Naph. Dist	64742-52-5
Mineral Spirits	Mixture
Propane / n-Butane.....	68476-86-8

Great for use by...

- Municipalities
- Refineries
- Shipyards
- Factories
- Mining Operations
- Power generating plants
- Chemical plants
- Industrial plants
- Factories
- Steel mills

Provides Protection For...

- Pipe threads
- Gaskets
- Motors
- Engines
- Bearings
- Gears
- Boilers
- Turbines
- Oil and ore drills
- Exhaust systems
- Heat exchangers
- Torque tools

DIRECTIONS: Surface must be free of dirt, grease and oil. Shake can until agitator ball begins to rattle freely for at least 30 seconds. In upright position, hold nozzle 8 to 10 inches from surface and apply by spraying RYBS in short bursts. Apply only enough to form a solid film over contact surfaces. Assemble and wipe off excess.

HMIS				NFPA		
Health	1	Severe	4	Extreme	Health.....	1
Flammability.....	3	Serious	3	High	Flammability.....	3
Reactivity.....	1	Moderate	2	Moderate	Reactivity.....	1
Personal Protection.....	G	Slight	1	Slight	Special Precautions.....	None
		Minimal	0	Insignificant		