

Vandal Mark Remover

Safety Data Sheet



SECTION 1: Product and company identification

Product name : Vandal Mark Remover
Use of the substance/mixture : Aerosol
Graffiti remover
Product code : 830801
Company : Share Corporation
P.O. Box 245013
Milwaukee, WI 53224 - USA
T (414) 355-4000
Emergency number : Chemtrec: (800) 424-9300

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Flam. Aerosol 1 H222
Acute Tox. 4 (Oral) H302
Acute Tox. 4 (Dermal) H312
Acute Tox. 4 (Inhalation) H332
Eye Irrit. 2A H319
Skin Sens. 1 H317
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS02

GHS07

Signal word (GHS-US) :

Danger

Hazard statements (GHS-US) :

Extremely flammable aerosol
Harmful if swallowed, in contact with skin or if inhaled
May cause an allergic skin reaction
Causes serious eye irritation

Precautionary statements (GHS-US) :

Keep away from heat, hot surfaces, open flames, sparks, Do not smoke. - No smoking
Do not spray on an open flame or other ignition source
Pressurized container: Do not pierce or burn, even after use
Avoid breathing fume, gas, mist, spray, vapors
Wash thoroughly after handling
Do not eat, drink or smoke when using this product
Use only outdoors or in a well-ventilated area
Contaminated work clothing must not be allowed out of the workplace
Wear eye protection, face protection, protective clothing, protective gloves
If swallowed: Call a doctor, a POISON CENTER, Do NOT induce vomiting if you feel unwell
If on skin: Wash with plenty of water
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
Call a doctor, a POISON CENTER if you feel unwell
Specific treatment (see First aid measures on this label)
Rinse mouth
If skin irritation or rash occurs: Get medical advice/attention
If eye irritation persists: Get medical advice/attention
Take off contaminated clothing and wash it before reuse
Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
Dispose of contents/container to comply with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Vandal Mark Remover

Safety Data Sheet



SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

Full text of H-phrases: see section 16

3.2. Mixture

Name	Product identifier	%	Classification (GHS-US)
acetone, propan-2-one, propanone	(CAS No) 67-64-1	30 - 50	Flam. Liq. 2, H225 Eye Irrit. 2A, H319 STOT SE 3, H336
Petroleum gases, liquefied	(CAS No) 68476-86-8	10 - 20	Not classified
xylene	(CAS No) 1330-20-7	10 - 15	Flam. Liq. 3, H226 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315
1-methoxy-2-propanol, monopropylene glycol methyl ether	(CAS No) 107-98-2	1 - 10	Flam. Liq. 3, H226 STOT SE 3, H336
dipropylene glycol monomethyl ether	(CAS No) 34590-94-8	1 - 10	Flam. Liq. 4, H227
(+)-limonene	(CAS No) 5989-27-5	1 - 5	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Asp. Tox. 1, H304
dibenzoyl peroxide, benzoyl peroxide	(CAS No) 94-36-0	1 - 5	Not classified

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : If you feel unwell, seek medical advice (show the label where possible).
- First-aid measures after inhalation : Artificial respiration and/or oxygen if necessary. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
- First-aid measures after skin contact : Wash with plenty of soap and water. Wash contaminated clothing before reuse.
- First-aid measures after eye contact : Rinse immediately with plenty of water. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do NOT induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries : Aspiration hazard Category 2. The liquid defats the skin. Depression of the central nervous system.
- Symptoms/injuries after inhalation : Overexposure may cause : Irritation of the respiratory tract. Headache. Dizziness. Unconsciousness. Central nervous system depression.
- Symptoms/injuries after skin contact : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: May cause moderate irritation. Dermatitis.
- Symptoms/injuries after eye contact : May cause slight irritation.
- Symptoms/injuries after ingestion : May be harmful if swallowed and enters airways.

4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry chemical powder. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Extremely flammable aerosol. Under fire conditions closed containers may rupture or explode.
- Explosion hazard : Vapors may travel long distances along ground before igniting/flashing back to vapor source. Explosion risk in case of fire.

5.3. Advice for firefighters

- Firefighting instructions : Exercise caution when fighting any chemical fire. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Use water spray or fog for cooling exposed containers.
- Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Eliminate every possible source of ignition. Gas is denser than air. May accumulate in low areas e.g. close to the ground. Vapors are heavier than air and may travel considerable distance to an ignition source and flash back to source of vapors.

6.1.1. For non-emergency personnel

- Protective equipment : Do not enter without an appropriate protective equipment.

Vandal Mark Remover

Safety Data Sheet



6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

6.2. Environmental precautions

Absorb and/or contain spill with inert material, then place in suitable container. Comply with local regulations for container disposal.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Clean contaminated surfaces with a soap solution. Take up liquid spill into absorbent material. This material and its container must be disposed of in a safe way, and as per local legislation.

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Clean contaminated clothing.

Hygiene measures : Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Pressurized container. Do not puncture, incinerate or crush.

Storage conditions : Store locked up.

Heat-ignition : KEEP SUBSTANCE AWAY FROM: ignition sources. heat sources.

Storage area : Aerosol 3.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

xylene (1330-20-7)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	150 ppm
ACGIH	Remark (ACGIH)	URT & eye irr; CNS impair
dipropylene glycol monomethyl ether (34590-94-8)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	ACGIH STEL (ppm)	100 ppm
acetone, propan-2-one, propanone (67-64-1)		
ACGIH	ACGIH TWA (ppm)	250 ppm
ACGIH	ACGIH STEL (ppm)	500 ppm
ACGIH	Remark (ACGIH)	eye irr; CNS impair; BEI
dibenzoyl peroxide, benzoyl peroxide (94-36-0)		
ACGIH	ACGIH TWA (mg/m ³)	5 mg/m ³
ACGIH	Remark (ACGIH)	URT & skin irr

8.2. Exposure controls

Personal protective equipment : Gloves. Face shield. Protective goggles. Protective clothing. Use appropriate personal protective equipment when risk assessment indicates this is necessary.



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Appearance : Aerosol. Liquid. Spray.
Odor : characteristic
Odor threshold : No data available
pH : No data available
Melting point : No data available

Vandal Mark Remover

Safety Data Sheet



Freezing point	: No data available
Boiling point	: 168 °C Product
Flash point	: -137 °F Propellant
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available
Vapor pressure	: No data available
Relative density	: No data available
Relative vapor density at 20 °C	: No data available
Specific gravity / density	: 0.867 g/ml Liquid
Solubility	: Poorly soluble in water
Log Pow	: No data available
Log Kow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
VOC content	: < 50 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

The product is stable at normal handling- and storage conditions.

10.3. Possibility of hazardous reactions

Hazardous polymerization does not occur.

10.4. Conditions to avoid

Aerosol containers are unstable at temperatures above 49°C. Avoid temperatures exceeding the flash point.

10.5. Incompatible materials

Oxidizing agent.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Harmful in contact with skin. Inhalation: Harmful if inhaled.

xylene (1330-20-7)	
LC50 inhalation rat (ppm)	4550 ppmV/4h
ATE CLP (dermal)	1100.000 mg/kg body weight
ATE CLP (gases)	4550.000 ppmV/4h
ATE CLP (dust, mist)	1.500 mg/l/4h
dipropylene glycol monomethyl ether (34590-94-8)	
LD50 oral rat	5135 mg/kg (Rat; Equivalent or similar to OECD 401; Literature study; >5000 mg/kg; Rat; Experimental value)
LD50 dermal rat	9500 mg/kg (Rat; Literature study; Equivalent or similar to OECD 402; >19020 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rabbit	9500 mg/kg (Rabbit; Literature study)
ATE CLP (oral)	5135.000 mg/kg body weight
ATE CLP (dermal)	9500.000 mg/kg body weight

Vandal Mark Remover

Safety Data Sheet



(+)-limonene (5989-27-5)	
LD50 oral rat	4400 mg/kg body weight (Rat; OECD 423: Acute Oral Toxicity – Acute Toxic Class Method; Literature study; > 2000 mg/kg bodyweight; Rat; Read-across)
LD50 dermal rabbit	> 5000 mg/kg body weight (Rabbit; Weight of evidence; Equivalent or similar to OECD 402)
ATE CLP (oral)	4400.000 mg/kg body weight

Skin corrosion/irritation	: Not classified.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

xylene (1330-20-7)	
IARC group	3 - Not Classifiable

(+)-limonene (5989-27-5)	
IARC group	3 - Not Classifiable

Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified.
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified
Symptoms/injuries after inhalation	: Overexposure may cause : Irritation of the respiratory tract. Headache. Dizziness. Unconsciousness. Central nervous system depression.
Symptoms/injuries after skin contact	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: May cause moderate irritation. Dermatitis.
Symptoms/injuries after eye contact	: May cause slight irritation.
Symptoms/injuries after ingestion	: May be harmful if swallowed and enters airways.

SECTION 12: Ecological information

12.1. Toxicity

dipropylene glycol monomethyl ether (34590-94-8)	
LC50 fish 1	> 10000 mg/l (96 h; Pimephales promelas; GLP)
LC50 other aquatic organisms 1	> 1000 mg/l (96 h; Crangon crangon)
LC50 fish 2	> 150 mg/l (72 h; Pisces)
Threshold limit other aquatic organisms 1	> 1000 mg/l (96 h; Crangon crangon)
Threshold limit algae 1	969 mg/l (72 h; Selenastrum capricornutum; GLP)
Threshold limit algae 2	> 969 mg/l (72 h; Selenastrum capricornutum; GLP)

(+)-limonene (5989-27-5)	
LC50 fish 1	720 µg/l (96 h; Pimephales promelas; Lethal)
EC50 Daphnia 1	0.36 mg/l (48 h; Daphnia magna; GLP)
LC50 fish 2	702 µg/l (96 h; Pimephales promelas)
Threshold limit algae 1	150 mg/l (72 h; Desmodesmus subspicatus; GLP)
Threshold limit algae 2	2.62 mg/l (72 h; Desmodesmus subspicatus)

12.2. Persistence and degradability

dipropylene glycol monomethyl ether (34590-94-8)	
Persistence and degradability	Readily biodegradable in water. No (test)data on mobility of the substance available. Photolysis in the air.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
ThOD	2.06 g O ₂ /g substance
BOD (% of ThOD)	0 % ThOD

(+)-limonene (5989-27-5)	
Persistence and degradability	Readily biodegradable in water. Forming sediments in water. Adsorbs into the soil.
ThOD	3.29 g O ₂ /g substance

12.3. Bioaccumulative potential

dipropylene glycol monomethyl ether (34590-94-8)	
Log Pow	0.0043 (Experimental value; OECD 102: Melting Point/Melting Range; 25 °C)

Vandal Mark Remover

Safety Data Sheet



dipropylene glycol monomethyl ether (34590-94-8)	
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).
(+)limonene (5989-27-5)	
BCF fish 1	864.8 - 1022 (Pisces; Fresh weight)
Log Pow	4.38 (Experimental value; OECD 117: Partition Coefficient (n-octanol/water), HPLC method; 37 °C)
Bioaccumulative potential	Potential for bioaccumulation (4 Log Kow > 5).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container to comply with local/regional/national/international regulations.

SECTION 14: Transport information

Department of Transportation (DOT)

Transport document description : UN1950 Aerosols (flammable, (each not exceeding 1 L capacity)), 2.1
 UN-No.(DOT) : UN1950
 Proper Shipping Name (DOT) : Aerosols
 flammable, (each not exceeding 1 L capacity)
 Transport hazard class(es) (DOT) : 2.1 - Class 2.1 - Flammable gas 49 CFR 173.115
 Hazard labels (DOT) : 2.1 - Flammable gas



DOT Packaging Non Bulk (49 CFR 173.xxx) : None
 DOT Packaging Bulk (49 CFR 173.xxx) : None
 DOT Special Provisions (49 CFR 172.102) : N82
 DOT Packaging Exceptions (49 CFR 173.xxx) : 306
 DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 75 kg
 DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 150 kg
 DOT Vessel Stowage Location : A
 DOT Vessel Stowage Other : 25 - Shade from radiant heat, 87 - Stow "separated from" Class 1 (explosives) except Division 14, 126 - Segregation same as for Class 9, miscellaneous hazardous materials

Additional information

Other information : No supplementary information available.

ADR

No additional information available

Transport by sea

No additional information available

Air transport

No additional information available

SECTION 15: Regulatory information

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

xylene	CAS No 1330-20-7	10 - 15
--------	------------------	---------

xylene (1330-20-7)

Vandal Mark Remover

Safety Data Sheet



xylene (1330-20-7)	
Listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	100 lb
acetone, propan-2-one, propanone (67-64-1)	
Not listed on SARA Section 313 (Specific toxic chemical listings)	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb

California Proposition 65 - This product contains, or may contain, trace quantities of a substance(s) known to the state of California to cause cancer and/or reproductive toxicity.

SECTION 16: Other information

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging.


Full text of H-phrases:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal) Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhalation) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Asp. Tox. 1	Aspiration hazard Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Aerosol 1	Flammable aerosol Category 1
Flam. Liq. 2	Flammable liquids Category 2
Flam. Liq. 3	Flammable liquids Category 3
Flam. Liq. 4	Flammable liquids Category 4
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H227	Combustible liquid
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H312	Harmful in contact with skin
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H336	May cause drowsiness or dizziness

NFPA health hazard : 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard : 4 - Will rapidly or completely vaporize at normal pressure and temperature, or is readily dispersed in air and will burn readily.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



Prepared by: Technical Department

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. No warranty is expressed or implied regarding the accuracy of this data or the results obtained from the use thereof. Our company assumes no responsibility for personal injury or property damage to the vendee, users or third parties caused by the material. Such vendees or users assume all risks associated with the use of this material.