



RCP

AERO

RUST RESISTANT PROTECTIVE COATING

**LONG-LASTING
MEETS MIL SPEC
C-16173D, GRADE 4 & C83933A**

DANGER:
Extremely Flammable Aerosol
Contains gas under pressure:
May explode if heated.

KEEP OUT OF REACH OF CHILDREN

See additional cautions on back panel.

NET WEIGHT: 12.5 Oz. (354 g)

This specially developed aerosol rust preventative combines the versatility and ease of aerosol application with the effectiveness and long term protection of metal parts. RCP AERO is a superior product consisting of a solvent based synthetic wax solution that supplies long term protection to metal parts exposed to weathering, high humidity or salt spray.

For indoor storage, a 2 or 3 mil coating will provide indefinite protection.

For outdoor storage, for 6 months to 1 year, apply a 2 or 3 mil coating. For protection for 1 to 2 years, apply a 5 or 6 mil coating.

A single application of this protective coating leaves a firm, waxy film which seals out moisture, dirt, and dust without cracking, blistering or pooling. Film is a transparent amber, easy to see through. Once product is dry, metal parts can be welded. Can be removed by washing with kerosene or mineral spirits. Once removed, parts can be painted.



DANGER:

Extremely Flammable Aerosol. Contains gas under pressure. May explode if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

PREVENTION:

Keep away from heat, sparks, open flames, and hot surfaces. - No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50° C/122° F. Store in a well-ventilated place. Wash hands thoroughly after handling. Wear protective gloves.

RESPONSE:

IF ON SKIN: Wash with plenty of water. If skin irritation occurs. Get medical attention. Take off contaminated clothing and wash before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

Avoid breathing fumes, mist, vapors, and spray. Use only outdoors or in a well-ventilated area.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center or doctor if you feel unwell.
IF SWALLOWED: Immediately call a poison center or doctor. Do NOT induce vomiting.

STORAGE:

Store locked up.

DISPOSAL:

Dispose of contents and container in accordance with local, state, and national regulations.

INGREDIENTS/CAS#:

Mineral Spirits (8052-41-3); Oxygenated Hydrocarbon (N/A); Propane/n-Butane (68476-86-8); Heptane (142-82-5)

NFPA® RATINGS:

Health: 1; Flammability: 3; Reactivity: 1

DIRECTIONS:

Clean parts of rust, scale, dirt or other contaminants. Remove cap, point opening in spray tip toward metal part to be protected. Hold can 8 to 10 inches away from metal parts and spray a 2 or 3 mil coating using a slow back and forth sweeping motion. For 5 or 6 mil coating, wait at least 5 minutes for first coat to dry, then reapply. Product dries completely in 2 hours and can be handled.

Sold by:

8345.030315