

# STARTING FLUID

## Aerosol Quick Start Fluid

**Form:** Liquid

**Color:** Clear

**Odor:** Strong Ethereal

**pH:** N/A

**Solubility (in water):** Negligible  
**(in mineral spirits):** Soluble

**VOC Content (% by wt):** Approx. 95

**Flash Point (ASTM D-7821):** N/A

**Specific Gravity:** <8.35 lbs/gal

**Density:** <1 g/cm<sup>3</sup>

**Storage Stability (at 70°F):** 1 year

**Ingredients**

**C.A.S. #**

Carbon Dioxide.....	8063-77-2
Diethyl Ether.....	60-29-7
Heptane.....	64742-49-0
Hydrotreated Naphthenic Distillates.....	64742-52-5

**Ideal for use in...**

- **Snow Blowers**
- **Recreational Vehicles**
- **Construction Equipment**
- **Trucks**
- **Lawn Mowers**
- **Farm Equipment**
- **Generators**
- **Automobiles**

**DIRECTIONS:** Spray STARTING FLUID directly into air cleaner or air intake for 5-10 seconds, then crank engine. It may be necessary to spray while engine is being cranked. If engine fails to start after a couple of minutes, stop, allow to rest for a few minutes then try again.

**DANGER: EXTREMELY FLAMMABLE. CONTENTS UNDER PRESSURE.** Keep away from heat, spark or open flame. Do not expose to temperatures above 120°F. Do not puncture or incinerate. Do not smoke while using. See product label for further cautions and first aid instructions.

HMIS			NFPA		
	Severe	4	Extreme		
Health.....	Serious	3	High	Health.....	2
Flammability.....	Moderate	2	Moderate	Flammability.....	4
Reactivity.....	Slight	1	Slight	Reactivity.....	1
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None