



PAINT STRIPPER Aerosol

PAINT & VARNISH REMOVER

VOC COMPLIANT

SAFE TO USE ON:

WOOD • CONCRETE • BRICK • IRON
STEEL • ALUMINUM, AND BRASS SURFACES

NET WEIGHT: 15 Oz. (425 g)

WARNING - EXTREMELY FLAMMABLE.

Extremely flammable aerosol. May be fatal if swallowed and enter airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeating exposure.

KEEP OUT OF REACH OF CHILDREN

See back panel for further cautions and first aid instructions.

Powerful **PAINT STRIPPER AEROSOL** removes most paint, varnish, shellac and protective coatings from many surfaces. Ensures fast, on-the-spot stripping without brushes, sprayers or rollers.



DANGER: Extremely flammable aerosol. May be fatal if swallowed and enter airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May damage fertility or the unborn child. May cause damage to organs through prolonged or repeating exposure.

PREVENTION: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use. Do not breathe gas. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 120°F(49°C). Dispose of contents/container in accordance with local/regional/national/international regulations.

RESPONSE:

IF SWALLOWED: Immediately call a poison center/doctor. Rinse mouth. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of water.

IF skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

IF eye irritation persists: Get medical advice/attention. Continue rinsing.

IF EXPOSED OR CONCERNED: Get medical advice/attention.

WARNING:

This product can expose you to propylene oxide, which is known to the State of California to cause cancer, and methanol, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

INGREDIENTS/CAS#:

Toluene (108-88-3); Propane (74-98-6); Butoxyethanol (111-76-2); Acetone (67-64-1); Butane (106-97-8); Diethylene Glycol Monobutyl Ether (112-34-5); Sodium Hydroxide (1310-73-2).

HMS® RATINGS:

Health: *3; Flammability: 3; Reactivity: 0; Personal Protection: X *=-Chronic

DIRECTIONS:

1. Spray **PAINT STRIPPER AEROSOL** uniformly over surface to be stripped. Strip a small section at a time.
2. Allow stripper to penetrate and loosen the paint film for 5 to 15 minutes. On thicker paint, a second application may be necessary for complete removal.
3. Remove the softened and blistered paint with a scraper, putty knife, cloth or strong water spray. **PAINT STRIPPER AEROSOL** is also water flushable.
4. Wipe surface clean, and allow to dry before repainting.

Sold by:

8580.121615

Share Corp. • P.O. Box 245013 • Milwaukee, WI 53224 • (800) 776-7192 • www.sharecorp.com