

ARMOR GUARD

High Gloss Protectant for Tires & Vinyl

Form: Aerosol

Color: No data available

Odor: No data available

pH: No data available

Solubility (in water): No data available
(in mineral spirits): No data available

VOC Content (% by weight): No data available

Flash Point (ASTM D-7821): -156°F

Specific Gravity: 0.745 g/ml estimated

Density: 6.22 lbs/gal estimated

Storage Stability (at 70°F): 1 year

Ingredients

C.A.S. #

Water.....	7732-18-5
Polydimethylsiloxane.....	63148-62-9
Butane.....	106-97-8
Propane.....	74-98-6
Mineral Oil.....	8042-47-5

Ideal for use on...

- **Tires**
- **Vinyl Tops**
- **Dashboards**
- **Airplanes**
- **Automobiles**
- **Camera Body's**
- **Boats**
- **Outdoor Furniture**
- **Computer Cases**
- **Laminated Surfaces**
- **Bicycles**
- **Lawn Equipment**

DIRECTIONS: Surfaces to be treated should first be wiped down to remove excess dust and any heavy soils. Surfaces to be treated should be completely dry. Spray ARMOR GUARD evenly on the clean, dry surface. Using a clean cloth, spread ARMOR GUARD evenly over the entire surface to be treated. Allow the product to penetrate the surface for a few minutes. Turn the clean cloth over and buff off any excess product.

HMIS®			NFPA®		
	Severe	4	Extreme		
Health.....	Serious	3	High	Health.....	1
Flammability.....	Moderate	2	Moderate	Flammability.....	4
Reactivity.....	Slight	1	Slight	Reactivity.....	0
Personal Protection.....	Minimal	0	Insignificant	Special Precautions.....	None